

Color: Bronze

Weight: 17.8 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	150W
120V	N/A	Color	3000K (Warm)
208V	N/A	Temp	
240V	N/A	Color Accuracy	82 CRI
277V	N/A	L70	
Input Watts	146.6/92.6/75.9W	Lifespan	100,000 Hours
		Lumens	19,467/12,904/10,648 lm
		Efficacy	132.8/139.4/140.3 lm/W

**Technical Specifications**

**Field Adjustability**

**Field Adjustable (Wattage):**

Field adjustable light output in 3 discrete steps: Medium Housing: 150W/90W/78W (factory default 150W)

**Compliance**

**UL Listed:**

Suitable for wet locations

**IP Rating:**

Ingress protection rating of IP66 for dust and water

**Dark Sky Conformance:**

Dark Sky Approved in 3000K. Conforms to (allows for conformance to) the IDA's fully shielding requirement, emitting no light above 90 degrees (with the exclusion of incidental light reflecting from fixture housing, mounts, and pole).

**Light Usage for Night Applications:**

This product has received the Design Lights Consortium's LUNA listing for 3000K Models. Designed to meet LUNA 5.1 requirements. LUNA Product Code: S-FXSLJR

**DLC Listed:**

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: S-FXSLJR

**LED Characteristics**

**LEDs:**

Long-life, high-efficacy, discrete, surface-mount LEDs

**Color Consistency:**

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

**Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

**Electrical**

**Driver:**

78W: Constant Current, Class 2, 480V, 50/60 Hz, 480V:0.20A

90W: Constant Current, Class 2, 480V, 50/60 Hz, 480V:0.23A

150W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.32A

**Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**THD:**

4.71% at 480V

**Power Factor:**

96% at 480V

**Surge Protection:**

Line to Line: 10kV  
Line to Ground: 6kV

**Performance**

**Lifespan:**

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Wattage Equivalency:**

Equivalent to 400W Metal Halide



## Technical Specifications (continued)

### Construction

#### IES Classification:

The Type IV distribution is especially suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. It produces a semicircular distribution with essentially the same candlepower at lateral angles from 90° to 270°.

#### Cold Weather Starting:

The minimum starting temperature is -40°C (-40°F)

#### Ambient Temperature :

Max Power Temp Rating: 40°C (104°F)  
 Middle Power Temp Rating: 52°C (125°F)  
 Low Power Temp Rating: 54°C (130°F)

#### Housing:

Die-cast aluminum

#### Mounting:

2 3/8" slipfitter mount with stainless steel hardware

#### Tilt Increment:

Rotates in 5 degree increments

#### Lens:

Polycarbonate lens

#### Reflector:

Aluminum reflector with white polycarbonate

#### Vibration Rating:

3G vibration rating per ANSI C136.31

#### Effective Projected Area:

1 Fixture: 0.37  
 2 Fixtures at 90°: 0.59  
 2 Fixtures at 180°: 0.74  
 3 Fixtures at 90°: 0.96  
 4 Fixtures at 90°: 0.96

#### Gaskets:

High-temperature silicone gaskets

#### Finish:

Formulated for high durability and long-lasting color

#### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Sensor Specifications

#### Multi Level Motion Sensor:

/WS2 sensor options use state-of-the-art surface mount technology (SMT), just like cellular phones and beepers. SMT gives you more reliability, greater RF immunity. This compact sensor that can fit neatly where others cannot. This sensor technology automatically affects the state of operation for lighting systems or individual luminaries based upon detecting the presence or absence of movement for both people as they exit/enter, or for the motion of moving vehicles within the sensors viewing area. The wide 180° viewing angle can detect movement along the entire side of a building with only one compact sensor. The hard lens is molded as part of the case, vandalproof, rainproof, bugproof and absolutely sealed. Sensor functions best when movement is across its detection pattern, not towards the sensor.

#### Optical

#### Bug Rating:

BUG Rating 150W: B2 U0 G3  
 BUG Rating 90W: B1 U0 G3  
 BUG Rating 78W: B1 U0 G3

#### Other


#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

Family	Housing Size	Distribution	Mounting	Color Temp	Finish	Voltage	Options
ALED	M	4T	SF	Y		/480	/WS2
	<b>S</b> = Small (80W/60W/40W) <b>M</b> = Medium (150W/90W/78W) <b>L</b> = Large (260W/220W/170W) <b>XL</b> = Extra Large (385W/345W/300W)	<b>2T</b> = Type II <b>3T</b> = Type III <b>4T</b> = Type IV <b>5T</b> = Type V <b>AT</b> = Auto Dealership Optic	<b>Blank</b> = Universal Pole Mount <b>SF</b> = Slipfitter <b>WM</b> = Wall Mount	<b>Blank</b> = 5000K Cool <b>N</b> = 4000K Neutral <b>Y</b> = 3000K Warm	<b>Blank</b> = Bronze <b>W</b> = White <b>B</b> = Black	<b>Blank</b> = 120-277V, 0-10V Dimming <b>/480</b> = 480V, 0-10V Dimming <sup>1</sup>	<b>Blank</b> = No Option <b>/7PR</b> = 7 Pin Twistlock Receptacle <b>/WS2</b> = Wattstopper, 20ft lens <b>/WS4</b> = Wattstopper, 40ft lens <sup>2</sup>

<sup>1</sup> 480V available in Medium, Large & Extra Large fixtures only

<sup>2</sup> Wattstopper option available in Large & Extra Large fixtures only