



Color: White

Weight: 36.3 lbs

|                     |              |
|---------------------|--------------|
| <b>Project:</b>     | <b>Type:</b> |
| <b>Prepared By:</b> | <b>Date:</b> |

| Driver Info |                  | LED Info       |                        |
|-------------|------------------|----------------|------------------------|
| Type        | Constant Current | Watts          | 385W                   |
| 120V        | 3.21A            | Color Temp     | 5000K (Cool)           |
| 208V        | 1.85A            | Color Accuracy | 85 CRI                 |
| 240V        | 1.60A            | L70 Lifespan   | 100,000 Hours          |
| 277V        | 1.39A            | Lumens         | 39253/42126/48702 lm   |
| Input Watts | 292/316.3/373.5W | Efficacy       | 134.4/133.2/130.4 lm/W |

## Technical Specifications

### Field Adjustability

#### Field Adjustable (Wattage):

Field adjustable light output in 3 discrete steps:  
Extra Large Housing: 385W/345W/300W/345W  
(factory default 385W)

### Compliance

#### UL Listed:

Suitable for wet locations

#### IP Rating:

Ingress protection rating of IP66 for dust and water

#### DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.  
DLC Product Code: S-NFIGRD

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, discrete, surface-mount LEDs

#### Color Consistency:

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

#### Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

#### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

### Electrical

#### Driver:

300W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 2.50A, 208V: 1.45A, 240V: 1.25A, 277V: 1.10A

345W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 2.88A, 208V: 1.66A, 240V: 1.44A, 277V: 1.25A

385W: Constant Current, Non-Class 2, 120-277V, 50/60 Hz, 120V: 3.21A, 208V: 1.85A, 240V: 1.60A, 277V: 1.39A

#### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

#### THD:

2.95% at 120V, 10.75% at 277V

#### Power Factor:

99.9% at 120V, 96.3% at 277V

#### Surge Protection:

Line to Line: 10kV  
Line to Ground: 6kV

#### 7-Pin Receptacle:

ANSI C136.41 7-pin receptacle, compatible with wireless control systems

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Wattage Equivalency:

Equivalent to 1,500W Metal Halide

### Construction

#### IES Classification:

The Type III distribution is meant to be located near the side of an area, projecting the light outward to fill the area. Ideal for roadways, general parking areas, lighting applications and where a large pool of light is required.

#### Cold Weather Starting:

The minimum starting temperature is -40°C (-40°F)



## Technical Specifications (continued)

### Ambient Temperature :

Max Power Temp Rating: 40°C (104°F)  
Middle Power Temp Rating: 43°C (110°F)  
Low Power Temp Rating: 47°C (116°F)

### Housing:

Die-cast aluminum

### Lens:

Polycarbonate lens

### Reflector:

Aluminum reflector with white polycarbonate

### Vibration Rating:

3G vibration rating per ANSI C136.31

### Effective Projected Area:

XL-EPA - Effective Projected Area-10137a 1 Fixture:  
0.6  
2 Fixtures at 90°: 0.96  
2 Fixtures at 180°: 1.2  
3 Fixtures at 90°: 1.56  
4 Fixtures at 90°: 1.56

### Gaskets:

High-temperature silicone gaskets

### Finish:

Formulated for high durability and long-lasting color

### Green Technology:

Mercury and UV free. RoHS-compliant components.

## Installation

---

### Mounting:

Wall mount

## Optical

---

### Bug Rating:

BUG Rating 385W: B4 U0 G4  
BUG Rating 345W: B3 U0 G4  
BUG Rating 300W: B3 U0 G4

## Other

---


### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

| Family | Housing Size  | Distribution  | Mounting  | Color Temp   | Finish  | Voltage  | Options   |
|--------|---|---|---|--|---|--|---|
| ALED   | XL  | 3T  | WM  |  | W   |  | /7PR  |
|        | <b>S</b> = Small (80W/60W/40W)<br><b>M</b> = Medium (150W/90W/78W)<br><b>L</b> = Large (260W/220W/170W)<br><b>XL</b> = Extra Large (385W/345W/300W) | <b>2T</b> = Type II<br><b>3T</b> = Type III<br><b>4T</b> = Type IV<br><b>5T</b> = Type V<br><b>AT</b> = Auto Dealership Optic | <b>Blank</b> = Universal Pole Mount<br><b>SF</b> = Slipfitter<br><b>WM</b> = Wall Mount | <b>Blank</b> = 5000K Cool<br><b>N</b> = 4000K Neutral<br><b>Y</b> = 3000K Warm | <b>Blank</b> = Bronze<br><b>W</b> = White<br><b>B</b> = Black | <b>Blank</b> = 120-277V, 0-10V Dimming<br><b>/480</b> = 480V, 0-10V Dimming <sup>1</sup> | <b>Blank</b> = No Option<br><b>/7PR</b> = 7 Pin Twistlock Receptacle<br><b>/WS2</b> = Wattstopper, 20ft lens<br><b>/WS4</b> = Wattstopper, 40ft lens <sup>2</sup> |

<sup>1</sup> 480V available in Medium, Large & Extra Large fixtures only  
<sup>2</sup> Wattstopper option available in Large & Extra Large fixtures only