
ARBAY2-95/480/LC/8C

RAB



Economical linear high bay delivers versatility and ultra-high efficiency. Available in 8 wattages and three sizes, for mounting heights ranging from 15 to 60 feet. Patent pending retractable design reduces volume by up to 60% to save valuable shelf and storage space.

Color: White

Technical Specifications

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics

LEDs:

Multi-chip, high-output, long-life LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Construction

Operating Temperature: -20°C (-4°F) to 50°C (122°F)

Housing:

22 gauge die formed with white powder coat finish. Y Hooks included for easy chain or cable mounting.

Reflector:

White painted, reflective, die formed painted steel

Lens:

Polycarbonate lens

Mounting:

V hooks and optional pendant mounting. AEROBAY[®] comes with two 42" chains.

Cord & Plug:

8 ft cord and no plug for 120-277V and 480V

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Lightcloud

Constant Current

N/A

N/A

N/A

N/A

Input Watts 90.9W

Project:

Prepared By:

Driver Info

Type 120V

208V

240V

277V

Lightcloud Controller Installed:

Integrated/embedded networked lighting control, luminaire-level lighting control. Fixture, Zone, and plug-load control from one powerful device. LLLC capable of switching, 0-10Vdimming, power/energy monitoring. Can also be used to extend the range of the Lightcloud mesh network communication protocols. Offers the capability to set the maximum light output to a less-than-maximum state of an individual luminaire at the time of installation or commissioning. The High-End trim functionality is field reconfigurable via the Lightcloud mesh network communication protocols. The Lightcloud controller can be attached to the fixture, junction box, or electrical panel. DLC system - N1XMLOEATBA

Type:

Date:

LED Info

Color Temp

L70 Lifespan

Lumens

Efficacy

Color Accuracy 83 CRI

95W

5000K (Cool)

100,000 Hours

13,421 lm

147.6

Watts

Learn more about Lightcloud.

Electrical

Driver: Class 2, Constant Current, 50/60 Hz, 480V: 0.195A

THD: 6.99% at 480V

Power Factor: 98.8% at 480V

Surge Protection: 6kV

ARBAY2-95/480/LC/8C

Technical Specifications (continued)

Other

Replacement: Replaces 6-lamp T8 or 250W MH

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Compliance

DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PUG73NFD



Features

High efficiency. Low price. Ideal for industrial warehouse spaces 100,000 hour LED lifespan 5-Year, limited warranty



ARBAY2-95/480/LC/8C

RAB

| RBAY 2 - 2 = 2 ft | - 95 95 = 95W 120 = 120W 145 = 145W 160 = 160W | Blank = 5000K Cool | /480 Blank = 120-277V, 0-10V Dimming | /LC Blank = No Options | | /8C |
|---------------------------------|--|-----------------------------|--|---|---|---|
| 2 = 2 ft | 120 = 120W 145 = 145W | Cool | , | Blank = No Options | a i i i i | |
| | | N = 4000K Neutral | /480 = 480V, 0-10V Dimming | /PIR = 120-277V, Passive Infrared Occupancy Sensor /LC = Lightcloud® Control /LCS = 120-277V, Lightcloud® Motion Sensor | Blank = No Options /E2 = 120-277V, Battery ¹ | Blank = No Options /SP10 = 10kV Surge Protection /8C = 8' Cord only ² /8CP = 8' Cord, Straight Blade Plug 120V, NEMA 5-15P ³ /8CP2 = 8' Cord, Straight Blade Plug 277V, NEMA 7-15P ³ /8CPT = 8' Cord, Twistlock Plug 120V, NEMA L5-15P ³ /8CPT2 = 8' Cord, Twistlock Plug 277V, NEMA L7-15P ³ /8CPT4 = 8' Cord, Twistlock Plug 480V, NEMA L8-20P ³ |