# ARCTP



Color: White

Weight: 0.7 lbs

| | |
|---|---|
| **Project:** | **Type:** |
| **Prepared By:** | **Date:** |

### Driver Info

| | |
|---|---|
| Type | Constant Current |
| 120V | 0.09A |
| 208V | N/A |
| 240V | N/A |
| 277V | N/A |
| Input Watts | 10.2W |

### LED Info

| | |
|---|---|
| Watts | 10W |
| Color Temp | 3000K |
| Color Accuracy | 93 CRI |
| L70 Lifespan | 100,000 Hours |
| Lumens | 837 lm |
| Efficacy | 82.1 |

## Technical Specifications

### Compliance

**UL Listed:**
Suitable for dry locations

**IP Rating:**
IP20

### LED Characteristics

**LEDs:**
Long-life, high-efficacy, COB (Chip on Board) LEDs

**Color Temperature:**
3000K

### Electrical

**Driver:**
Constant Current, Class 2, 120V, 60 Hz, 120V: 0.10A

**Dimming Driver:**
120V TRIAC Dimmers

**Aux Power Supply:**
No

**Dim to Off:**
No

**Surge Protection:**
Ring Wave L-N:2.5 kV, LN-PE 2.5 kV

### Emergency Characteristics

**Cold Weather Starting w/Battery Backup:**
The minimum starting temperature is -4°F (-20°C)

### Construction

**Maximum Ambient Temperature:**
Suitable for use in up to 104°F (40°C)

**Housing:**
Aluminum

**Reflector:**
Polycarbonate

**Finish:**
Formulated for high durability and long-lasting color

### Performance

**Lifespan:**
100,000-Hour LED lifespan based on IESlm-80 results and TM-21 calculations

### Installation

**Mounting:**
H-Track Pendant Mount

### Optical


**Optics:**
36°

### Other

**5-Year Limited Warranty:**
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

## Dimensions




## Ordering Matrix

| Family | Wattage | Mounting | Color Temp | Optics | Finish | Driver |
|---|---|---|---|---|---|---|
| ARC | | TP | | | | |
| | **Blank =** 10W | **Blank =** H-Track Mount<br>**SM =** Surface Mount<br>**TP =** H-Track Pendant Mount<br>**PM =** Pendant Mount<br>**RM =** Semi-Recessed Mount | **Blank =** 3000K | **Blank =** 36° | **Blank =** White Housing/Gold Reflector<br>**B =** Black Housing/Gold Reflector | **Blank =** 120V, TRIAC Dimming |


Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice