




Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	360W
120V	2.98A/2.12A/1.52A	Color Temp	4000/5000K
208V	1.73A/1.30A/0.87A	Color Accuracy	83-86 CRI
240V	1.50A/1.13A/0.75A	L70 Lifespan	100,000 Hours
277V	1.27A/0.94A/0.70A	Lumens	27,222-49,779 lm
Input Watts	175-355.9W	Efficacy	137.2-155.6 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:

Field Adjustable Light Output:
360W with 3 Power Preset:
100% (360W), 75% (270W), and 50% (180W)
Color Temperature Selectable:
4000K and 5000K(factory default 4000K)

Compliance

UL Listed:

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-8VZGVK

LED Characteristics

LEDs:

Long-life, high-efficacy, discrete, surface-mount LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Electrical

Driver:

100% Power: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 2.98A, 208V: 1.73A, 208V: 1.50A, 277V: 1.27A
75% Power: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 2.12A, 208V: 1.30A, 208V: 1.13A, 277V: 0.94A
50% Power: Constant Current, Class 1, 120-277V, 50/60Hz, 120V: 1.52A, 208V: 0.87A, 208V: 0.75A, 277V: 0.70A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

9.78% at 120V, 7.98% at 277V

Power Factor:

99.5% at 120V, 96.5% at 277V

Surge Protection:

6 kV

Construction

Cold Weather Starting:

The minimum starting temperature is -20°C (-4°F)

Maximum Ambient Temperature:

Suitable for use in up to 122°F(50°C)

Lens:

Polycarbonate lens

Reflector:

Polyethylene Terephthalate (PET)

Housing:

Aluminum

Technical Specifications (continued)

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Installation

Mounting:
Comes standard with V-hooks for chain mounting.
Accessories available for pendant and surface
mounting (purchased separately).

Lightcloud

Input Voltage:
12VDC

Operating Frequency:
50/60Hz

Input Current @ 12V (mA):
30mA

Operating Temperature:
-40°F to 140°F (-20°C to 60°C)

Dimming:
Yes, when connected to a compatible 0-10V driver

Mounting Height:
40 ft

Detection Range:
40 ft diameter mounted at 40 ft

Sensor:
Passive Infrared (PIR)

Default Setting:
Uncommissioned State:
Motion Sensitivity: High
Brightness when triggered: 100%
Hold time: 1 minute
Standby to dim: 20%
Standby time: 1 minute
When vacant: Off

Commissioned State:
Motion Sensitivity: High
Brightness when triggered: Last on status
Hold time: 20 minutes
When vacant: Off

Occupied Actions:
On or On at a Dim Level

Vacant Options:
Off or On at a Dim Level

Occupancy Timeout:
1 minute to 240 minutes


Daylight Sensing:
The sensor will determine to trigger the light(s) on or
not based on the daylight threshold level set in the
Lightcloud Blue mobile app.

Environment:
Suitable for dry, damp, or wet environments in
indoor applications

IP Rating:
IP65

Other
5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from
defects in materials and workmanship for a period of
five (5) years from the date of delivery to the end
user, including coverage of light output, color
stability, driver performance and fixture finish. RAB's
warranty is subject to all terms and conditions found
at rablighting.com/warranty.

Dimensions



Features

- 0-10V Dimming, standard
- 100,000-hour LED lifespan
- DLC Premium listed
- 5-Year, no-compromise warranty

Ordering Matrix

Family	Wattage (Length)	Color Temp	Driver	Sensor	Battery Backup
AR	L			/PIR	/E
XS = 95/71/48W (1.5') S = 160/120/80W (2') M = 275/206/138W (3') L = 360/270/180W (4')		Blank = 4000/5000K CCT Adjustable	Blank = 120-277V, 0-10V Dimming /480 = 480V, 0-10V Dimming	Blank = None /MVS = Microwave Occupancy Sensor /PIR = Passive Infrared Sensor /LCBS/MVS = Lightcloud Blue Microwave Occupancy Sensor /LCBS = Lightcloud Blue Passive Infrared Sensor	Blank = None /E = Battery Backup