B11-5-E12-940-F-C

RAB Residential



Project:	Туре:
Prepared By:	Date:

Technical Specifications

Performance Product Type:

Decorative
Input Wattage:

5W

Lumens (Nominal): 500lm

L70 Lifespan: 15,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency: 60W

LED Characteristics

Color Accuracy (CRI): 90 CRI

Color Temperature: 4000K

Electrical

Power Factor: >0.7

Dimmable: Yes, down to 10% Input Voltage: 120V

Operating Frequency: 60 Hz

Operating Temperature: -20°C to 40°C

Construction

Bulb Shape: B11

Enclosure Material: Glass

Housing Finish: Clear

Base Type: E12

Optical

Beam Angle: 360°

Other

Technology EQ: Incandescent

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Compliance

Listings: UL Listed

Environment/Fixture Rating: Wet / Enclosed

Energy Star Approved: This product is ENERGY STAR[®] Version 2.0 Certified

Energy Star ID: 2366764

B11-5-E12-940-F-C

Technical Specifications (continued)

T20 Compliant:

Yes, Title 20 Tier 2

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Model Number for Certification:


B11-5-E12-940-F-C

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity		
6	1		

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	0	0	0	0
PALLET	3180	0	0	0



Features

Replacement for conventional decorative lamps

Filament LED construction gives a unique traditional look and feel for decorative and ambient applications

Produces rich and vibrant colors, >90CRI

Rated for use in enclosed and open fixtures in dry and damp locations

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

Title 20 Compliant, ENERGY STAR Compliant, UL Listed

Smooth uniform dimming down to 10% (check dimmer compatibility list)

B11-5-E12-940-F-C

Ordering Matrix

Family	Wattage	Base Type	CRI/Color Temp	Туре	Finish
B11	5	E12	940	F	С
	3 = 3W 5 = 5W		940 = 90 CRI, 4000K 930 = 90 CRI, 3000K 927 = 90 CRI, 2700K	F = Filament	C = Clear F = Frosted