



LED bollard with architectural quality and strength at an affordable price point. Cylindrical post with round head. Available in 4 light pattern configurations including 360° (24W), 270° (18W), 180° (12W option) & 90° (12W standard).

Color: White

Weight: 22.0 lbs

Project:

Type:

Prepared By:

Date:

### Driver Info

Type	Constant Current
120V	0.26A
208V	0.18A
240V	0.15A
277V	0.14A
Input Watts	22.5W

### LED Info

Watts	24W
Color Temp	5100K (Cool)
Color Accuracy	73 CRI
L70 Lifespan	100,000 Hours
Lumens	2,724 lm
Efficacy	121.1 lm/W

## Technical Specifications

### Compliance

#### UL Listed:

Suitable for wet locations. Suitable for mounting within 4 ft (1.2m) of the ground.

#### IESNA LM-79 & lm-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA lm-79 and lm-80

### LED Characteristics

#### LEDs:

Long-life, high-efficiency, surface-mount LEDs

#### Color Consistency:

5-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

#### Color Stability:

LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period

#### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Wattage Equivalency:

Equivalent to 70W Metal Halide

### Optical

#### BUG Rating:

B2 U3 G2

### Construction

#### Cold Weather Starting:

The minimum starting temperature is -40°C (-40°F)

#### Thermal Management:

Cast aluminum Thermal Management system for optimal heat sinking. The BLEDR is designed for cool operation, maximum efficiency and long life by minimizing LED junction temperature.

#### Housing:

Die-cast aluminum with extruded aluminum post

#### Lens:

Frosted vandal resistant polycarbonate

#### Reflector:

Vacuum-metalized polycarbonate

### Mounting:

Four (4) anchor bolts provided for concrete pad mounting. Internal base support has leveling screws.

### Gaskets:

High-temperature silicone gaskets seal out moisture gaskets seal out moisture

### Anchor Bolt:

Anchor Bolt Dimension is available [here](#).

### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color

### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Other

#### Patents:

The design of BLEDR is protected by patents in US, Canada & China

## Technical Specifications (continued)

### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

### Electrical

#### Driver:

Constant Current, Class 2, 100-277V, 50/60 Hz, 4kV Surge Protection, 720mA, 120V: 0.26A, 208V: 0.18A, 240V: 0.15A, 277V: 0.14A


#### THD:

4.52% at 120V, 5.67% at 277V

#### Power Factor:

99.6% at 120V, 93.5% at 277V

## Dimensions



## Features

- Patented base mount design for super sturdy installation
- Durable construction and frosted vandal-resistant polycarbonate lens
- 4 configurations to provide 360°(24W), 270°(18W), 180°(12W) or 90°(12W) lighting pattern
- Precision-engineered optics deliver maximum downward lighting without glare
- Four leveling screws provided for easy installation
- 100,000-hour LED lifespan

## Ordering Matrix

Family	Wattage	Color Temp	Finish		Distribution	Voltage	Dimming	Backup
BLEDR	24		W	-				
	12 = 12W 18 = 18W 24 = 24W	Blank = 5000K Cool N = 4000K Neutral Y = 3000K Warm	Blank = Bronze W = White K = Black		Blank = Standard <sup>1</sup> 180 = 180 degrees (12W only)	Blank = No Option (120-277V) /480 = 480V (24W only) <sup>2</sup>	Blank = None (Standard) /D10 = 0-10V Dimming	Blank = No Battery Backup /E = Battery Backup (24W only) <sup>3</sup> /EC = Battery Backup Cold Weather (24W only) <sup>3</sup>

<sup>1</sup> Standard Distributions: 24W = 360Å°, 18W = 270Å°, 12W = 90Å° \*

<sup>2</sup> 480VAC available for 24W fixture versions - offered with /D10 dimming option as standard

<sup>3</sup> Only for 24W, 120-277VAC fixture versions