

Project:

Type:

Prepared By:

Date:

**Driver Info****LED Info**

Type	Constant Current	Watts	30/21/18/15/9W
120V	0.25A/0.18A/0.16A/0.13A/0.08A	Color Temp	3000/3500/4000K
208V	0.15A/0.12A/0.11A/0.10A/0.07A	Color Accuracy	93-95 CRI
240V	0.13A/0.10A/0.09A/0.08A/0.06A	L70 Lifespan	100,000 Hours
277V	0.12A/0.09A/0.08A/0.07A/0.05A	Lumens	1280-4057 lm
Input Watts	9.7-30.2W	Efficacy	128-141.1 lm/W

**Technical Specifications****Field Adjustability****Field Adjustable:**

Field Adjustable Light Output:  
30/21/18/15/9W (factory default 30W)  
Color Temperature Selectable:  
3000K, 3500K and 4000K (factory default 3500K)

**Compliance****UL Listed:**

Suitable for damp locations

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**IP Rating:**

IP20

**Electrical****Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**Surge Protection:**

1 kV L-L 2kV L/N-G

**Continuous Runs:**

Maximum wattage for a continuous run should not exceed 600W

**LED Characteristics****LEDs:**

Long-life, high-efficacy, surface-mount LEDs

**Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

**Performance****Lifespan:**

100,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations

**Construction****Cold Weather Starting:**

The minimum starting temperature is -4°F (-20°C)

**Maximum Ambient Temperature:**

Suitable for use in up to 104°F (40°C)

**Housing:**

Sheet metal and extruded aluminum

**Lens:**

Frosted polycarbonate lens

**Reflector:**

Polyethylene Terephthalate (PET)

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

**Installation****Mounting:**

94" of aircraft cable provided with cable grippers for easy adjustment after installation


**Continuous Runs:**

Yes, connect multiple fixtures (up to 600W) end-to-end for continuous illumination.

**Other****5-Year Limited Warranty:**

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Dimensions**



**Features**

- 100,000-Hour LED lifespan
- 0-10V dimming
- 5-Year, limited warranty

**Ordering Matrix**

Family	Size/Wattage	Mounting	Color Temp	Lens	Distribution	Finish	Driver
BOAE	3	P				W	
	2 = 2 ft, 20/14/12/10/6W 3 = 3 ft, 30/21/18/15/9W 4 = 4 ft, 40/28/24/20/12W 8 = 8 ft, 80/56/48/40/24W	P = Pendant Mount	Blank = 3000/3500/4000K CCT Adjustable	Blank = Flat Lens	Blank = Downlight	W = White S = Silver B = Black	Blank = 120-277V, 0-10V Dimming