




Project:	Type:
Prepared By:	Date:

Technical Specifications

Compliance

Buy American Act Compliance:

This product complies with the Buy American Act

The Build America, Buy America Act (BABA):

Light poles meet The Build America, Buy America Act (BABA) (Pub. L. No. 117- 58, §§ 70901-52).

Construction

Pole Material:

Reinforced fiberglass

Maximum EPA Per Wind Zone:

90 mph: 2.2
100 mph: 0.4

Height:

25 ft

Shape:

Square

Finish:

All poles come with bronze finish and 3-layer of protection against UV degradation. The third layer is the thermally bonded outer coating.

Pole Drilling:

All poles HH covers and cable entry are factory drilled

Hand Hole and Covers:

2 1/2" x 5" hand hole is standard for all the poles and are located at 18" above ground level. The hand hole covers are made of durable, weather resistant material.

Tenons:

The aluminum tenon is pre-assembled to the pole before shipping.

Anchor Bolt Templates:

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available [online](#).

Other

2-Year Limited Warranty:

The RAB 2-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](#).


Accessories:

Poles are shipped with tenon. Die-cast aluminum anchor base included. The anchor bolt kit, base covers for square poles are sold separately BOLT4/7: Anchor bolt kit for round poles.BCK-CP-S: Square composite pole base cover.

Terms of Sale:

Pole Terms of Sale is available [online](#).

Dimensions



Features

- Complies with Buy America Act
- 2-Year, limited warranty

Ordering Matrix

Family	Shape	Height	Drilled/Welded Tenon
C	S	25	WT
S = Square 15 = 15 ft D = Drilled 20 = 20 ft WT = Welded Tenon 25 = 25 ft			