

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



### Features and Benefits

- Illuminates entire LED load at reduced output under emergency mode
- One Piece Design with Metal Housing
- 2-in-1 LED test switch and indicator light included
- Evaluated to UL 924 requirements
- Not for use with dimmers
- 90 Minute operation in Emergency Mode
- UL Listed
- Operating Temperature: 32°F/0°C to 122°F/50°C

Technical Specifications	
<p><b>Performance</b></p> <p><b>L70 Lifespan:</b> 50,000-Hour LED lifespan based on IES LM-70 results</p> <p><b>Construction</b></p> <p><b>Bulb Shape:</b> Cuboid</p> <p><b>Enclosure Material:</b> Metal</p> <p><b>Electrical</b></p> <p><b>Input Voltage:</b> 120-277V AC</p> <p><b>Operating Frequency:</b> 50/60Hz</p> <p><b>Operating Temperature:</b> 0°C to 50°C</p>	<p><b>Other</b></p> <p><b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a>.</p> <p><b>Compliance</b></p> <p><b>Listings:</b> UL Listed</p> <p><b>Environment/Fixture Rating:</b> Damp</p> <p><b>T20 Compliant:</b> Yes</p> <p><b>RoHS:</b> Mercury and UV free. RoHS-compliant components.</p> <p><b>FCC:</b> Complies with Part 15B of the FCC Rules</p>

## Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
14	1

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	1	0	0	0
PALLET	1500	0	0	0