

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Compatible with RAB Type C T8 LED Lamps only
- Meets FCC Part 15 (Class B) Consumer Limits
- Short Circuit Overload and Open Load Protection
- Suitable for Dry and Damp Locations
- UL8750 Recognized Component
- Dimmable with 0-10V Dimmer
- Maximum Case Temperature: 75°C/167°F
- Input Frequency: 50/60 Hz
- THD: < 20%
- Type P
- Output Class 2

Technical Specifications		Other
Electrical THD: <20% Power Factor: >0.9 Input Voltage: 120-277V AC Input Frequency: 50/60 Hz Input Power (Max): 26W Max. Standby Power: 1W Output Current: 260mA*2 Max Output Voltage: 30-45V No-Load Voltage: 56V dc Max.	Efficiency: >85% Operating Temperature: -20°C/-4°F to 45°C/113°F Dimming: 0-10V Dimming Construction Storage Temperature: -30°C/-22°F to 80°C/176°F Protection: Open circuit protection, over voltage protection, short circuit protection Reduced Lamp Load: Parallel output for each channel, support N and N-1 application Compliance Certifications: Class P, UL8750, Output Class 2	Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.7	8.1	8
PALLET	1140	39	40.5	43.1

Dimension

