ECOMBO34-GR





| Project: | Туре: |
|--------------|-------|
| Prepared By: | Date: |

Technical Specifications

Performance

Product Type:

Exit Combo

Description:

Ultra-economy exit sign combo with 90-minute emergency battery backup unit.

Input Wattage:

1.6W @120V; 1.6W @277V

Electrical

Power Factor:

0.11@120V; 0.05@277V

Input Voltage:

Dual 120/277Vage

Operating Frequency:

60Hz

Input Current @ 120V (mA):

120--- 1

Maximum Output Wattage:

1W

Operating Temperature:

32°F to 104°F (0°C to 40°C)

Emergency Illumination:

90 minutes

Battery Backup:

Battery Backup

Battery Type:

Nickel Cadmium

Battery Voltage:

3 6V

Recharge Time Required:

24-hours

Storage Temperature:

68°F to 86°F (20°C to 30°C)

Storage Shelf Life:

3 years before the initial charge. 5 years after initial charge.

Self Diagnostics:

Manual Test

Installation

Mounting Method:

Back/Top

Mounting Type:

Wall/Ceiling Mount

Maximum Mounting Height (ft.):

8 f

Cold Weather Rated:

No

Emergency Egress Coverage(ft) Mounting at

height of 7.5ft:

14 ft x 3 ft mounted @ 7.5 ft

Construction

Shape:

Rectangle

Housing Material:

Thermoplastic

Panel Material:

Thermoplastic

Panel Color:

White

Letter Color:

Green

Housing Finish:

White

Number of Faces:

Universal Single/Double Face

ECOMBO34-GR



Technical Specifications (continued)

Arrow Direction:

Field installable chevrons included

Sign Format:

Stencil

Remote Capacity:

Yes

No. of Heads:

2-Lamp Heads

Head Shape:

Round

Remote Head Power (W):

0.5W

Remote Head Lumens (Lm):

42lm

Remote Heads Replaceable:

Yes

Remote Power (W) Capacity:

0.5W

Compliance

Listings:

UL924 Listed

Environment:

Suitable for indoor use in dry and damp environments

Model Number for Certification:

CEU3GWRC-V2

T20 Compliant:

Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:

Not applicable

California Energy Commission (CEC) Status:

Lawful for Sales in California

FCC:

Complies with Part 15B of the FCC Rules

Other

5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Battery is prorated.


Note:

All values are typical (tolerance +/- 10%)

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.





| Family Face Heads Exit Sign Letter Color High Lumen Remote Capable ECOMBO34 G G R Blank = Universal Faces Blank = 2 Heads G = Green RG = Red/Green Selectable R = Remote Capable R = Remote Capable | Ordering Matrix | | | | | |
|---|-----------------|-------------------------|-----------------|------------------------|------------|----------------|
| Blank = Universal Faces Blank = 2 Heads Blank = Red G = Green H = High Lumen R = Remote Capable R = Remote Capable | Family | Face | Heads | Exit Sign Letter Color | High Lumen | Remote Capable |
| G = Green $H = High Lumen$ $R = Remote Capable$ | ECOMBO34 | | | G | | R |
| | | Blank = Universal Faces | Blank = 2 Heads | G = Green | | • |