EXITOUT-G





Project:	Туре:
Prepared By:	Date:

Technical Specifications

Performance

Product Type:

Outdoor Exit Sign

Description:

Outdoor exit sign with a single face and green letters. Wet rated.

Input Wattage:

2.7W

Electrical

Power Factor:

≥0.9

Input Voltage:

Dual 120/277 Voltage

Operating Frequency (Hz):

60Hz

Input Current @ 120V (mA):

25mA

Input Current @ 277V (mA):

11mA

Dual Voltage Circuit Operation:

No

Operating Temperature:

-4°F to 122°F (-20°C to 50°C)

Battery Backup:

No, AC only

Battery Operating Temperature:

-20°F to 50°F (-4°C to 122°C)

Storage Temperature:

68°F to 86°F (20°C to 30°C)

Self Diagnostics:

No, manual test only

Remote Test Switch:

No

Installation

Mounting Method:

Back/Top/End

Mounting Type:

Wall/Ceiling Mount

Cold Weather Rated:

No

Construction

Shape: Rectangle

Housing Material:

Thermoplastic

Panel Material:

Thermoplastic

Panel Color:

White

Letter Color:

Green

Housing Color:

White

Number of Faces:

Single Face

Arrow Direction:

No Arrow

Sign Format:

Stencil

Remote Capacity:

No

Compliance

Listings:

UL924 Listed, NFPA 101 (current Life Safety Code), NEC and OSHA illumination standards

EXITOUT-G



Technical Specifications (continued)

Environment:

Suitable for indoor or outdoor use in dry, damp, and wet environments

IP Rating:

Outdoor

Certification Model Number:

WLEZXTEU1GW

T20 Compliant:

Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:

Not applicable

California Energy Commission (CEC) Status:

Lawful for Sales in California

FCC:


Complies with Part 15 of the FCC Rules

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

Single-face panel with color letters

Durable thermoplastic design

Rated for us indoor and outdoor in dry, damp, and wet environments.

Compliant with California Title 20

EXITOUT-G



Family Face Exit Sign Letter Color Panel Housing Cold Weather EXITOUT G Blank = 1 Face Blank = Red G = Green Blank = White Panel Blank = White Housing C = Cold Weather	Ordering Mat	rix				
Blank = 1 Face Blank = Red Blank = White Panel Blank = White Housing Blank = Wet Location Rated	Family	Face	Exit Sign Letter Color	Panel	Housing	Cold Weather
	EXITOUT		G			
		Blank = 1 Face		Blank = White Panel	Blank = White Housing	