### EZLED78SFB44W/BL

# RAB



This 78W spotlight combines high lumen output and a concentrated narrow beam distribution to illuminate objects up to 80 feet away with brilliant precision. Ideal for lighting large flags, tall building façades and signage.

Color: White

Weight: 26.6 lbs

### **Technical Specifications**

#### Other

**EZLED78SF with Bi-Level Operation:** Allows 33%-66%-100% output modes

#### Note:

All values are typical (tolerance +/- 10%)

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

#### Patents:

The design of EZLED is protected by patents in U.S. Pat D679,856, and pending patents in Canada, China, Taiwan and Mexico.

#### **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

#### Compliance

UL Listed: Suitable for wet locations. Suitable for ground mounting.

#### DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: P8XV163K

#### Construction

**Effective Projected Area:** EPA = 1.2

**Cold Weather Starting:** The minimum starting temperature is -40°C (-40°F)

**Maximum Ambient Temperature:** Suitable for use in up to 40°C (104°F)

Thermal Management: Superior thermal management with external "Air-Flow" fins

Housing: Precision die-cast aluminum housing and door frame

Driver Info	LED Info
Prepared By:	Date:
Project:	Туре:

Туре	Constant Current	Watts	78W
120V	0.67A	Color Temp	5000K (Cool)
208V	0.38A	Color Accuracy	72 CRI
240V	0.33A	L70 Lifespan	100,000 Hours
277V	0.31A	Lumens	8,516 lm
Input Watts	78W	Efficacy	109.2 lm/W

Mounting:

2 3/8" slipfitter mount with stainless steel hardware

Lens: Tempered glass

Reflector:

Vacuum-metalized, specular thermoplastic

#### Gaskets:

High-temperature silicone

Finish:

Formulated for high durability and long-lasting color

Green Technology: Mercury and UV free. RoHS-compliant components.

**Tilt Increment:** Rotates in 6 degree increments

LED Characteristics

LEDs: Three multi-chip, high-output, long-life LEDs

Color Consistency: 7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

## EZLED78SFB44W/BL

# RAB

### **Technical Specifications (continued)**

#### **Color Stability:**

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

#### **Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

#### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Optical

#### NEMA Type:

NEMA Beam Spread of 4H x 4V

#### Electrical

#### Driver:


Constant current, Class2, 100-277V. 50/60 Hz, 6kV Surge Protection, 120-277V, 120V: 0.67A, 208V: 0.38A, 240V: 0.33A, 277V: 0.31A

#### THD:

2.68% at 120V, 8.16% at 277V

#### **Power Factor:**

99.8% at 120V, 92.6% at 277V



#### Features

High powered narrow beam spotlight Illuminates objects at a distance of 80 feet Available in NEMA type 3H x 3V and 4H x 4V Trunnion or slipfitter mounting options available Outperforms equivalent MH fixtures

## EZLED78SFB44W/BL

## RAB

Family	Wattage	Mounting	Color Temp	Distribution	Finish	Voltage	Dimming	Control Options
EZLED	78	SF		B44	W		/BL	
	<b>78</b> = 78W	SF = Slipfitter T = Trunnion	Blank = 5000K Cool N = 4000K Neutral Y = 3000K Warm	Blank = NEMA 3H x 3V B44 = NEMA 4H x 4V	Blank = Bronze W = White	Blank = 120-277V	Blank = None (Standard) /D10 = 0-10V Dimming /BL = Bi-Level	Blank = No Option /PC = 120V Button Photocell /PC2 = 277V Buttor Photocell /PCS = 120V Swive Photocell /PCS2 = 277V Swive Photocell /PCT = 120-277V Twistlock Photocel