



Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	40W
120V	0.33A	Color Temp	2700-6500K
208V	0.19A	Color Accuracy	80-86 CRI
240V	0.17A	L70 Lifespan	N/A
277V	0.14A	Lumens	4,909-5,050 lm
Input Watts	41.7-42.7W	Efficacy	115.1-121.1 lm/W

Technical Specifications			
Field Adjustability Field Adjustable: Field Adjustable Light Output: 40W/30W/25W (factory default: 40W) Color Temperature Selectable: 3500K, 4000K and 5000K (factory default:4000K)		Dimming Driver: Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.	
Compliance UL Listed: Suitable for damp locations		THD: 2.69% at 120V, 7.97% at 277V	
IESNA LM-79 & LM-80 Testing: RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA lm-79 and lm-80		Power Factor: 99.6% at 120V, 93.9% at 277V	
Trade Agreements Act Compliant: This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act		Aux Power Supply: No	
Electrical Driver: Constant Current, Class II, 120-277V, 50/60 Hz: 40W: 120V: 0.33A, 208V: 0.19A, 240V: 0.17A, 277V: 0.14A 30W: 120V: 0.25A, 208V: 0.14A, 240V: 0.13A, 277V: 0.11A 25W: 120V: 0.21A, 208V: 0.12A 240V: 0.10A, 277V: 0.09A		Dim to Off: Yes	
		Surge Protection: 2 kV + 4 kV	
		Construction Cold Weather Starting: The minimum starting temperature is -22°F (-30°C)	
		Maximum Ambient Temperature: Suitable for use in up to 104°F (40°C)	
		IC Rated: Suitable for direct contact with insulation	
		Lens: Precision engineered polystyrene diffuser provides high uniformity, and reduced glare. No visible diodes, hot-spots, or shadows.	
		Housing: Aluminum+Iron	
		Reflector: TPET reflective paper	
		Finish: Formulated for high durability and long-lasting color	
		Green Technology: Mercury and UV free. RoHS-compliant components.	
		Installation Mounting: Surface, suspended & recessed mounting. The mounting accessories sold separately.	
		Installation: Standard integral T-bar clips secure the fixture to T-bars and prevent T-system separation	
		LED Characteristics LEDs: Long-life, high-efficacy, surface-mount LEDs	

Technical Specifications (continued)

Color Stability:

LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Lightcloud

Lightcloud Blue:

Lightcloud Blue is a Bluetooth Mesh wireless lighting control system that allows you to control RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and large commercial applications using the Lightcloud Blue mobile app. Each device in a system can communicate with any other device, eliminating the need for a Gateway or Hub and maximizing the control system's reach.

DLC system - N1XMLOEATBA (Interior);
NHCZ2BIA17L (Exterior)

Learn more at www.lightcloud.com.

Gateway Required:

No

Communication Protocol:

Bluetooth Mesh

Range:

Up to 60 feet between standard building materials. Building materials such as brick, concrete, and steel construction may require additional Lightcloud Blue devices to extend around an obstruction. Up to 200 feet clear line of sight (varies by device).

Spacing Criteria:

Lightcloud Blue devices should be placed within the specified range to communicate within the Bluetooth Mesh network.

Factory Reset:

Method 1: Delete from App

Open the app and access the device settings for the paired device. Be sure that the device is online and select 'Delete'. The device will flash on/off 5 times and return to full brightness.

Method 2: Manual

Power the device off and on 5x consecutively. Do not allow less than 4s to elapse from switching off to on. Do not allow more than 2s to elapse from switching on to off. The device will flash 3x, then reset to 100% brightness at default CCT.

Method 3: Rapid Reset Tool

The Rapid Reset process must be done by a professional electrician qualified by RAB. Reach out to your RAB sales manager to request a Rapid Reset Tool. The tool simply needs to be placed directly on the back of the fixture for 2s or until the lamp/luminaire flashes 3x, then resets to 100% brightness at the default CCT.

SmartShift

SmartShift:

SmartShift is the most advanced - yet easiest to use - circadian lighting system, which syncs white color tuning with the local sunrise and sunset. Requires the NANO/LCB (sold separately)

Sensor Settings

Sensor Connection Type:

RJ09

Max Mounting Height:

9 ft

Detection Range:

20 ft diameter at 9 ft mounting height

Sensor Technology:

Passive Infrared (PIR)

Default Setting:

Uncommissioned State:

Motion Sensitivity: High
Brightness when triggered : 100%
Hold time: 20 minutes
Standby to dim: 20%
Standby time: 1 minute
When vacant: Off
Daylight: Disabled

Commissioned State:

Once pair, the sensor will default to disabled. Once enabled the following settings apply:
Motion Sensitivity: High
Brightness when triggered: Last on status
Hold time: 20 minutes
Standby to dim: 20%
Standby time: 1 minute
When vacant: Off
Daylight: Disabled

Adjustable Sensor Settings?:

Yes, using the Lightcloud Blue mobile app

Sensing Type:

Occupancy, Vacancy

Occupied Actions:

On or On at a Dim Level

Vacant Actions:

Off or On at a Dim Level

Occupancy Timeout:

1 minute to 240 minutes

Daylight Sensing:

Closed loop daylight harvesting with continuous dimming. Specify settings using the Lightcloud Blue mobile app.

High/Low Dim Level:

The High Dim Level (HDL) is limited to 50%-70%


The Low Dim Level (LDL) is limited to 20%-70%

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- 100,000-hour LED Lifespan
- DLC Standard Listed
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size	Wattage	Driver	Color Temp	Options	Output
EZP	1X4				/LCBS	
	2X2 = 2' x 2'	2X4 = 50/40/30W	/D10 = 0-10V Dimming	Blank = 3500/4000/5000K CCT	/LCBS/MVS = Lightcloud Blue w/MVS	Blank = High
	2X4 = 2' x 4'	1X4 = 40/30/25W	Blank = 120-277V, 0-10V	Adjustable	Sensor	Output
	1X4 = 1' x 4'	2X2 = 40/30/25W	Dimming	Tunable White 2700-6500K*	/LCBS/MVS/E2 = Lightcloud Blue w/MVS	
					Sensor and Battery Backup	
					/LCBS/E2 = Lightcloud Blue w/PIR Sensor	
					and Battery Backup	
					/LCB/E2 = Lightcloud Blue and Battery	
					Backup	
					/E2 = Battery Backup	
					/LCBS = Lightcloud Blue w/PIR Sensor	
					/LCB = Lightcloud Blue	
					/LCS = Lightcloud Sensor	
					/LC = Lightcloud	
					Blank = No Option	