



Compact, tough and good looking cast aluminum housing with hinged framed glass lens. Integra Hood glare shield and stainless steel clip. Lamp supplied.

Color: Bronze

Weight: 9.9 lbs

Project:	Type:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type	32w Triple	Type	Elec HPF QT
Watts	32W	120V	N/A
Shape/Size	N/A	208V	N/A
Base	N/A	240V	N/A
ANSI	N/A	277V	0.13A
Hours	12,000	Input Watts	32W
Lamp Lumens	2,400 lm		
Efficacy	75 lm/W		

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations

Electrical

Battery Backup:

Bodine "Coldpak" will operate the CFL lamp for 90 minutes if power fails. Rated -20°C to +55°C. Battery is a maintenance free NiCad with 7 - 10 year life. Wired for 277V.

Sockets:

Porcelain with all copper current carrying components

Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts

Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts

Construction

Housing:

Precision die-cast aluminum, 1/2" NPS threaded arm with locking swivel fits all standard mounting boxes

Reflector:

Anodized semi-specular aluminum

Lens:

Thermal tempered shock resistant glass

Lens Gasket:

High-temperature tubular silicone set in die cast retaining groove remains in place during relamping

Finish:

Formulated for high durability and long-lasting color

Ballast Minimum Starting Temperature:

0 Deg F

Other

Patents:

Pat. D420,458.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

