



Specification grade HID floodlight with cutting edge design, architectural quality, superior features and mounting options at competitive prices.

Color: Bronze

Weight: 8.8 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Lamp Info		Ballast Info	
Type	Triple 32W	Type	Electronic QT
Watts	32W	120V	0.3A
Shape/Size	N/A	208V	0.21A
Base	N/A	240V	0.16A
ANSI	N/A	277V	0.13A
Hours	12,000	Input Watts	36W
Lamp Lumens	2,400 lm		
Efficacy	66.7 lm/W		

**Technical Specifications**

**Compliance**

**UL Listed:**

Suitable for wet locations. Suitable for ground mounting.

**Construction**

**Housing:**

Precision die-cast aluminum. 1/2" NPS locking Swivel Arm, Wall Bracket Trunnion or Slip Fitter.

**Reflector:**

Anodized aluminum. Field adjustable beam spread. Rotates 90° for horizontal or vertical lamp position.

**Lens Frame & Glare Shield:**

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

**Finish:**

Formulated for high durability and long-lasting color

**Lens:**

Thermal tempered shock resistant glass, 3/16" thick

**Lens Gasket:**

High-temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping.

**Ground Mounting:**

Use the new MPM19 PVC Mighty Post with aluminum cap for sturdy installation

**EPA:**

Maximum EPA 1.1

**Electrical**

**Socket:**

CFL Plug in type, GX24q-4 base

**Other**

**Patents:**

Pat. D545,472

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

