



Specification grade HID floodlight with cutting edge design, architectural quality, superior features and mounting options at competitive prices.

Color: Bronze

Weight: 8.8 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

| | |
|-------------|------------|
| Type | Triple 84W |
| Watts | 84W |
| Shape/Size | N/A |
| Base | N/A |
| ANSI | N/A |
| Hours | 12,000 |
| Lamp Lumens | 6,400 lm |
| Efficacy | 69.6 lm/W |

Ballast Info

| | |
|-------------|---------------|
| Type | Electronic QT |
| 120V | 0.6A |
| 208V | 0.6A |
| 240V | 0.5A |
| 277V | 0.4A |
| Input Watts | 92W |

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for ground mounting.

Construction

Housing:

Precision die-cast aluminum. 1/2" NPS locking Swivel Arm, Wall Bracket Trunnion or Slip Fitter.

Reflector:

Anodized aluminum. Field adjustable beam spread. Rotates 90° for horizontal or vertical lamp position.

Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Finish:

Formulated for high durability and long-lasting color

Lens:

Thermal tempered shock resistant glass, 3/16" thick

Lens Gasket:

High-temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping.

Ground Mounting:

Use the new MPM19 PVC Mighty Post with aluminum cap for sturdy installation

EPA:

Maximum EPA 1.1

Electrical

Socket:

CFL Plug in type, GX24q-4 base

Other

Patents:

Pat. D545,472

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

