



Color: Bronze

Weight: 36.8 lbs

|              |       |
|--------------|-------|
| Project:     | Type: |
| Prepared By: | Date: |

| Driver Info |                  | LED Info       |                  |
|-------------|------------------|----------------|------------------|
| Type        | Constant Current | Watts          | 346/213W         |
| 120V        | 2.84A            | Color Temp     | 4000/5000K       |
| 208V        | 1.67A            | Color Accuracy | 84-86 CRI        |
| 240V        | 1.45A            | L70 Lifespan   | 100,000 Hours    |
| 277V        | 1.25A            | Lumens         | 30,483-46,300 lm |
| Input Watts | 217.1-354.3W     | Efficacy       | 121.7-145.6 lm/W |

Technical Specifications

Field Adjustability

**Field Adjustable:**  
Field Adjustable Light Output:  
346W/213W (factory default 346W)  
Color temperature (selectable by 4000K and 5000K)

Compliance

**UL Listed:**  
Suitable for wet locations. Suitable for mounting within 4 ft (1.2m) of the ground.

**IP Rating:**  
Ingress protection rating of IP66 for dust and water

**IESNA LM-79 & LM-80 Testing:**  
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**Trade Agreements Act Compliant:**  
This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

**DLC Listed:**  
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.  
DLC Product Code: S-K4LY03

LED Characteristics

**LEDs:**  
Long-life, high-efficacy, discrete, surface-mount LEDs

**Color Consistency:**  
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**  
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

**Color Uniformity:**  
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

Electrical

**Driver:**  
213W: Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 1.78A, 208V: 1.03A, 240V: 0.89A, 277V: 0.77A

346W: Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 2.84A, 208V: 1.67A, 240V: 1.45A, 277V: 1.25A

**Dimming Driver:**  
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

**THD:**  
7.25% at 120V, 6.97% at 277V

**Power Factor:**  
99.7% at 120V, 96.4% at 277V

**Surge Protection:**  
6 kV

**Performance**  
**Lifespan:**  
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

**Wattage Equivalency:**  
346W: 1000W Metal Halide  
213W: 750W Metal Halide

**Optical**  
**NEMA Type:**  
NEMA Beam Spread 3H x 3V

**Construction**  
**Cold Weather Starting:**  
The minimum starting temperature is -40°F (-40°C)

**Ambient Temperature :**  
Max Power Temp Rating: 104°F (40°C)  
Low Power Temp Rating: 49.7°C (121.5°F)

## Technical Specifications (continued)

**Housing:**

Die-cast aluminum

**Tilt Increment:**

Rotates in 30 degree increments

**Lens:**

Ultra clear, tempered glass

**Reflector:**

Vacuum metalized polycarbonate

**Vibration Rating:**

3G vibration rating per ANSI C136.31

**Effective Projected Area:**

EPA = 0.59

**Gaskets:**

High-temperature silicone gaskets

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

### Installation

---

**Mounting:**

Heavy-duty Trunnion mount with stainless steel hardware


### Other

---

**10-Year, No-Compromise Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

Dimensions



Features

- 100,000-hour life based on LM-80 results and TM-21 calculations
- DLC Premium Listed
- IP66 Rating protects against dust & water ingress
- 10-Year, No-Compromise Warranty

Ordering Matrix

| Family | Housing Size                                                                                                                             | Color Temp                        | NEMA Type                                                                                           | Mounting                        | Finish                      | Driver                                                        | Options                                      |
|--------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------|---------------------------------------------------------------|----------------------------------------------|
| FXLED  | M                                                                                                                                        |                                   | B33                                                                                                 | T                               |                             |                                                               |                                              |
|        | XS = Field Adjustable 80/60/40W<br>S = Field Adjustable 168/132/97/69W<br>M = Field Adjustable 346/213W<br>L = Field Adjustable 534/445W | Blank = 4000/5000K CCT Adjustable | Blank = 6H x 6V (XS&S) or 7H x 6V (M&L)<br>B33 = 3H x 3V <sup>1</sup><br>B55 = 5H x 5V <sup>1</sup> | SF = Slipfitter<br>T = Trunnion | Blank = Bronze<br>W = White | Blank = 120-277V, 0-10V Dimming<br>/480 = 480V, 0-10V Dimming | Blank = No Option<br>/7PR = 7-Pin receptacle |

<sup>1</sup> Available on medium (M) and large (L) sizes only