




<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	26W
120V	0.25A	Color Temp	3000K (Warm)
208V	0.16A	Color Accuracy	82 CRI
240V	0.14A	L70 Lifespan	100,000 Hours
277V	0.12A	Lumens	1,230 lm
Input Watts	28.9W	Efficacy	42.6 lm/W

## Technical Specifications

<p><b>Compliance</b></p> <p><b>UL Listed:</b> Suitable for wet locations. Suitable for mounting within 4ft (1.2m) of the ground.</p> <p><b>IESNA LM-79 &amp; lm-80 Testing:</b> RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA lm-79 and lm-80</p> <p><b>Performance</b></p> <p><b>Lifespan:</b> 100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations</p> <p><b>Wattage Equivalency:</b> Equivalent 120W Incandescent, 75W Metal Halide or 42W CFL</p> <p><b>Construction</b></p> <p><b>Fixture:</b> The GN3LED26YRADW comes with the GOOSE3W Arm</p> <p><b>Housing:</b> Precision die-cast aluminum housing, lens frame and mounting plate</p> <p><b>Gaskets:</b> High-temperature Silicone</p>	<p><b>Mounting:</b> Heavy-duty mounting arm with "O" ring seal and stainless steel screw</p> <p><b>Cold Weather Starting:</b> The minimum starting temperature is -40°C (-40°F)</p> <p><b>Shades:</b> 15" Angled Dome Shade offered</p> <p><b>Finish:</b> Formulated for high durability and long-lasting color</p> <p><b>Green Technology:</b> Mercury and UV free. RoHS-compliant components.</p> <p><b>LED Characteristics</b></p> <p><b>LED:</b> Single multi-chip, 26W high-output, long-life LED</p> <p><b>Color Stability:</b> LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period</p> <p><b>Color Uniformity:</b> RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.</p>	<p><b>Electrical</b></p> <p><b>Driver:</b> Constant Current, Class 2, 100-277V, 50/60 Hz, 0.48 A, THD≤20%, PF 97.9%.</p> <p><b>Surge Protection:</b> 4kV</p> <p><b>Other</b></p> <p><b>Patents:</b> The design of the Gooseneck is protected by patents pending in US, Canada, China and Taiwan</p> <p><b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a>.</p> <p><b>Buy American Act Compliance:</b> RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.</p>
---	--	---

## Dimensions



## Features

- Adjustable 45° swivel joint
- Superior heat sink
- Die-cast aluminum housing
- 5-Year, No-Compromise Warranty

## Ordering Matrix

Family	Wattage	Color Temp	Reflector	Shade	ShadeSize	Finish
GN3LED	26	Y	R	AD		W
	13 = 13W 26 = 26W	Y = 3000K Warm N = 4000K Neutral	Blank = Flood R = Rectangular S = Spot	AD = Angled Dome	11 = 11" Blank = 15"	B = Black W = White A = Bronze S = Silver G = Hunter Green YL = Yellow LB = Light Blue BL = Royal Blue BWN = Brown I = Ivory R = Red