



Color: Gray Weight: 20.1 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Hazardous Location Classifications

UL 844:
Electric lighting fixtures for use in hazardous (classified) locations

Class 1, Division 2 (Groups A, B, C, D):
Class 1 (Hazardous Material in Surrounding Atmosphere):
Flammable vapors or gases may be present

Division 2 (Presence of Hazardous Materials):
Ignitable concentrations of hazards exist only under accidental system breakdowns or abnormal operating conditions

Groups A, B, C, D (Hazardous Material in Surrounding Atmosphere):
A = Acetylene
B = Hydrogen, butadiene, ethylene oxide, propylene oxide and acrolein
C = Ethylene, cyclopropane and ethyl ether
D = Acetone, ammonia, benzene, butane, ethanol, gasoline, hexane, methane, methanol, naphta, natural gas, propane & toluene

Class 2, Division 1 (Groups E, F, G):
Class 2 (Hazardous Material in Surrounding Atmosphere):
Combustible dust

Division 1 (Presence of Hazardous Materials):
Ignitable concentrations of hazards exist only under normal operating conditions

Groups E, F, G (Hazardous Material in Surrounding Atmosphere):
E = Combustible metal dust: aluminum, commercial alloys, magnesium
F = Combustible carbonaceous dust: carbon black charcoal, coal, coke dusts
G = Other combustibles dusts: chemicals, flour, grain, plastic, and wood

Class 2, Division 2 (Groups F, G):
Class 2 (Hazardous Material in Surrounding Atmosphere):
Combustible dust

Division 2 (Presence of Hazardous Materials):
Ignitable concentrations of hazards exist only under accidental system breakdowns or abnormal operating conditions

Groups F, G (Hazardous Material in Surrounding Atmosphere):
F = Combustible carbonaceous dust: carbon black charcoal, coal, coke dusts
G = Other combustibles dusts: chemicals, flour, grain, plastic, and wood

Class 3:
Class 3 (Hazardous Material in Surrounding Atmosphere):
Easily ignitable flyings or fibers may be present

Compliance
UL 924:
Charge Time: 24 hours
Emergency Run Time: 90 min

UL Listed:
Suitable for wet locations

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNAIm-79 andIm-80.

IP Rating:
Ingress protection rating of IP66 for dust and water

Construction
Cold Weather Starting:
The minimum starting temperature is 0°C (32°F)

Maximum Ambient Temperature:
Suitable for use in up to 104°F (40°C)



Technical Specifications (continued)

Housing:

Aluminum

Lens:

Glass

Gaskets:

High-temperature silicone

Green Technology:

Mercury and UV free. RoHS-compliant components.

Finish:

Formulated for high durability and long-lasting color

LED Characteristics

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Color Consistency:

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Electrical

Driver:

Constant Current, Class 1, 120-277V, 50/60 Hz, 120V: 0.10A, 208V: 0.06A, 240V: 0.05A, 277V: 0.04A

Surge Protection:

L-N:1 kV

L/N-FG:2 kV

Aux Power Supply:

No

Dim to Off:

No

Performance

Lifespan:

50,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations


Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.



Dimensions



Features

- UL 1598 and 844
- IP66 Rating protects against dust & water ingress
- 100,000-Hour LED lifespan
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Hazardous Location	Mounting	Finish	Driver	Letter Color
HAZEXIT					/G
	Blank = C1D2	Blank = Wall Mount Kit + Stainless-steel tether cable	Blank = Gray	Blank = 120-277V	Blank = Red Letter /G = Green Letter