



Color: Gray Weight: 36.5 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	200W
120V	1.70A	Color Temp	5000K
208V	0.99A	Color Accuracy	71 CRI
240V	0.85A	L70 Lifespan	100,000 Hours
277V	0.74A	Lumens	30,794 lm
Input Watts	202.2W	Efficacy	152.3

Technical Specifications

Hazardous Location Classifications

Class I:
Class I: A hazardous location in which flammable gases or vapors may be present in the air in sufficient quantities to be explosive or ignitable, such as petroleum refineries, aircraft hangars, dry cleaning plants, utility gas plants or storage areas for liquified petroleum or natural gas, and spray finishing areas.

Division 1:
Division 1: (Presence of Hazardous Materials): Ignitable concentrations of hazards exist only under normal operating conditions

Division 2:
Division 2: Abnormal condition, where ignitable concentrations of flammable gases, vapors or liquids are not like to exist under normal operating conditions, for example:

Closed storage drums containing flammable liquids in an inside storage room would not normal allow the hazardous vapors to escape into the atmosphere. But if one of the containers is leaking, you've got an abnormal condition.

Groups A - D:
Groups A - D: The gases and vapors of Class 1 locations are broken into four groups by the Code: A,B,C, and D. These materials are grouped according to the ignition temperature of the substance, its explosion pressure, and other flammable characteristics.

Group A - The only substance in group A is acetylene because it is a gas with extremely high explosion pressures.

Group B - This group includes hydrogen and other materials with similar characteristics.

Group C & D - The most usual Class 1 groups. They comprise the greatest percentage of all Class I hazardous locations. Found in Group C is ethylene. Found in Group D are many of the most common flammable substances such as butane, gasoline, natural gas and propane.

NEC/CE T-Code (Class 1, Div 1, Group C,D):
T5

NEC/CE T-Code (Class 1, Div 2, Group A, B, C,D):
T4

UL 1598:
Electric lighting fixtures for use in non-hazardous locations

UL 844:
Electric lighting fixtures for use in hazardous (classified) locations

Compliance

UL Listed:
Suitable for wet locations. Suitable for mounting within 4 ft (1.2m) of the ground.

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

IP Rating:
Ingress protection rating of IP66 for dust and water

DLC Listed:
This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-048XB9

Electrical

Driver:
Constant Current, Class 1, 120-277V, 50/60 Hz, 120V: 1.70A, 208V: 0.99A, 240V: 0.85A, 277V: 0.74A

Dimming Driver:
Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

Technical Specifications (continued)

THD:
5.4% at 120V, 4.3% at 277V

Power Factor:
99.5% at 120V, 95.5% at 277V

Surge Protection:
L/N-G 10 kV, L-N 6 kV

Optical
NEMA Type:
7H x 6V Beam Spread

Construction
Cold Weather Starting:
The minimum starting temperature is -40°F (-40°C)

Maximum Ambient Temperature:
Suitable for use in up to 131°F (55°C)

Housing:
Die-cast aluminum

Reflector:
Polycarbonate

Lens:
Clear glass + 7Hx6V polycarbonate lens

Effective Projected Area:
EPA = 0.67

Gaskets:
High-temperature silicone

Green Technology:
Mercury and UV free. RoHS-compliant components.

Vibration Rating:
3G vibration rating per ANSI C136.31

Finish:
Formulated for high durability and long-lasting color

LED Characteristics
LEDs:
Long-life, high-efficacy, surface-mount LEDs


Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Color Consistency:
7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Performance
Lifespan:
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Other
5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- Class 1, Division 1, Groups C, D
- Class 1, Division 2, Groups A, B, C, D
- IP66 Rating protects against dust & water ingress
- DLC Listed
- 100,000-Hour LED lifespan
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Wattage	Mounting	Color Temp	NEMA Type	Finish	Driver
HAZFX	200					
	30 = 30W 60 = 60W 100 = 100W 150 = 150W 200 = 200W	Blank = Yoke SF = Slipfitter	Blank = 5000K	Blank = 7H x 6V	Blank = Gray	Blank = 120-277V, 0-10V Dimming /480 = 480V, 0-10V Dimming