

Project:

Type:

Prepared By:

Date:



UPC: 019813700656

Features and Benefits

- Replacement for traditional Metal Halide or High Pressure Sodium HID Lamps
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- Lightweight design
- Omnidirectional light output
- 25,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Recognized
- Non-Dimmable
- 3 Year Limited Warranty

Technical Specifications

Performance

Product Type:

HID Replacement

Input Wattage:

26W

Lumens (Nominal):

3,450lm

L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:

50W

LED Characteristics

Color Accuracy (CRI):

80

Color Temperature:

5000K

Electrical

Power Factor:

>0.9

Dimmable:

Non-Dim

Input Voltage:

120-277V AC

Operating Frequency:

60 Hz

Operating Temperature:

-20°C to 40°C

Construction

Bulb Shape:

T-Shape

Enclosure Material:

Plastic

Housing Finish:

White

Base Type:

E26 Edison

Optical

Beam Angle:

180°

Installation

Installation Method:

UL Type B, Ballast Bypass

Burning Position:

Universal

Other

Technology EQ:

Metal Halide or High Pressure Sodium

3 Yr Limited Warranty:

The RAB 3-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty

Compliance

Listings:

UL Recognized

Technical Specifications (continued)

Environment/Fixture Rating:

Damp / Enclosed

IP Rating:

IP64

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Model Number for Certification:

H10043(HID-26-E26-850-BYP-TS)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
20	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	360	0	0	0

Dimension

