

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



### Features and Benefits

- Replacement for traditional Metal Halide or High Pressure Sodium HID Lamps
- Ideal for wall pack retrofit applications
- Optimized for Horizontal Applications with Directional Light Output and Rotatable base
- Active Cooling: Internal sensor overheat and engaged will automatically reduce output to 70% rated wattage until the sensor cools and will light up again to 100%
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- 4kV surge protection built in
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Listed, UL Classified, DLC Listed
- Non-Dimmable
- 5 Year No Compromise Warranty

Technical Specifications		
<b>Performance</b> <hr/> <b>Product Type:</b> HID Replacement	<b>For Use Outdoors in Open Fixtures:</b> No	<b>Operating Frequency:</b> 50/60Hz
<b>Input Wattage:</b> 40W	<b>LED Characteristics</b> <hr/> <b>Color Temperature:</b> 4000K Cool White	<b>Input Current @ 120V:</b> 0.4mA
<b>Wattage Equivalency:</b> 200W HID	<b>Color Accuracy (CRI):</b> 80 CRI	<b>Flicker:</b> <30%
<b>Lumens (Nominal):</b> 6,200lm	<b>Electrical</b> <hr/> <b>THD:</b> <20%	<b>Optical</b> <hr/> <b>Beam Angle:</b> 180°
<b>Efficacy:</b> 155lm/W	<b>Power Factor:</b> >0.9	<b>Other</b> <hr/> <b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a> .
<b>L70 Lifespan:</b> 50,000 Hours	<b>Operating Temperature:</b> -30°C to 60°C	<b>Installation</b> <hr/> <b>Installation Type:</b> Type B, Ballast Bypass
<b>Construction</b> <hr/> <b>Bulb Shape:</b> Wall Pack	<b>Dimmable:</b> No	
<b>Base Type:</b> E26 Edison	<b>Input Voltage:</b> 100-277V	

## Technical Specifications (continued)

### Installation Orientation:

Universal Installation

### Compliance

#### UL Listed:

Yes

#### UL Classified:

Yes

#### DLC Product Code:

NO DLC CATEGORY

#### California Energy Commission (CEC) Status:

Lawful for Sales in California



## Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
8	1


## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	16.7	16.7	11
PALLET	288	47.7	35.4	39.4

## Wiring Diagram



## Dimension



## Light Distribution

