HID-54-EX39-850-BYP/3SP

Project:	Туре:	Prepared By: C	Date:
	Image: Window StructureImage: Window Structu	Features Replaces traditional metal halide o Lamp includes on board low-voltag accessories Rated for use in enclosed and oper 4kV surge protection built in 50,000-Hour lifespan 5-Year, No-Compromise Warranty	ge AUX port for lamp level sensor

Technical Specifications

Performance

Product Type: HID Replacement

Input Wattage: 54W

Lumens (Nominal): 8,100lm

Efficacy: 150lm/W

L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency: 200W Metal Halide or High Pressure Sodium

Compliance UL Listed:

Suitable for damp locations

Enclosed Fixtures: Suitable for use in enclosed fixtures Model Number for Certification: H10070(HID-54-EX39-850-BYP/3SP)

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLCUHX2SNULC

LED Characteristics

Color Temperature: 5000K

Color Accuracy (CRI): >80 CRI

Electrical

THD: <20%

Power Factor: >0.9

Dimmable: Yes Flicker: <30%

Operating Temperature: -30°C to 60°C

Input Voltage: 100-277V

Operating Frequency: 50/60Hz

Construction

Bulb Shape: Post top (sensor)

Base Type: EX39

Endcap Material: Metal

Enclosure Material: Polycarbonate $\mathsf{D}\mathsf{A}\mathsf{P}$

HID-54-EX39-850-BYP/3SP

Technical Specifications (continued)

Optical

Beam Angle: 360°

Installation

Installation Orientation:

Vertical and Horizontal

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
8	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	15.4	11.8	15
PALLET	432	48	40	45.77

