

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replaces traditional metal halide or high pressure sodium HID lamp
- Adjustable wattage and CCT allows for in-field customization
- Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed fixtures in dry or damp locations
- 4kV surge protection built in
- 50,000-Hour lifespan
- Environmentally friendly, no mercury used
- UL Listed, DLC Listed (select models)
- 5-Year, No-Compromise Warranty

Technical Specifications		
<p>Performance</p> <p>Product Type: HID Replacement</p> <p>Input Wattage: 8.8-135W</p> <p>Lumens (Nominal): 1,300-20,000lm</p> <p>Efficacy: 147.7-148.1lm/W</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p> <p>Wattage Equivalency: 400W Metal Halide or High Pressure Sodium</p> <p>Compliance</p> <p>UL Listed: Suitable for damp locations</p> <p>Enclosed Fixtures: Suitable for use in enclosed fixtures</p>	<p>Model Number for Certification: H10077(HIDFA-135S-V-EX39-8CCT-BYP)</p> <p>DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLV4B3FLLDON</p> <p>LED Characteristics</p> <p>Color Temperature: 3000K/4000K/5000K</p> <p>Color Accuracy (CRI): 80 CRI</p> <p>Electrical</p> <p>THD: <20%</p> <p>Power Factor: 0.9</p> <p>Dimmable: Stepless dimming by rotate switch</p>	<p>Operating Temperature: -30°C to 50°C</p> <p>Input Voltage: 120-277V</p> <p>Operating Frequency: 60 Hz</p> <p>Construction</p> <p>Bulb Shape: Round</p> <p>Base Type: EX39</p> <p>Endcap Material: Aluminum</p> <p>Enclosure Material: Plastic</p> <p>Optical</p> <p>Beam Angle: 90°</p>

Technical Specifications (continued)

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	2	17.5	14.4	18
PALLET	36	44.49	36.61	45.67

Dimension

