

Project: Type: Prepared By: Date:



UPC: 192552005098

#### **Features and Benefits**

Replaces traditional metal halide or high pressure sodium HID lamp

Adjustable wattage and CCT allows for in-field customization

Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast

Rated for use in enclosed fixtures in dry or damp locations

4kV surge protection built in

50,000-Hour lifespan

Environmentally friendly, no mercury used

UL Listed, DLC Listed (select models)

5-Year, No-Compromise Warranty

### **Technical Specifications**

Performance

**Product Type:** 

HID Replacement

Input Wattage:

5W/10W/20W

Lumens (Nominal):

800/1,600/3,200lm

Efficacy:

160lm/W

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:

100W Metal Halide or High Pressure Sodium

Compliance

**UL Listed:** 

Suitable for damp locations

**Enclosed Fixtures:** 

Suitable for use in enclosed fixtures

**LED Characteristics** 

**Color Temperature:** 

3000K/4000K/5000K

Color Accuracy (CRI):

>80 CRI

**Electrical** 

THD:

<20%

Power Factor: >0.9

**Dimmable:** Yes

Flicker:

<30%

**Operating Temperature:** 

-30°C to 60°C

Input Voltage:

100-277V

**Operating Frequency:** 

50/60Hz

Construction

**Bulb Shape:** 

Wall Pack

Base Type:

EX39

Endcap Material:

Metal

**Enclosure Material:** 

Polycarbonate

Optical

Beam Angle:

180°

Installation

Installation Orientation:

Horizontal



## **Technical Specifications (continued)**

#### Other

## Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

## Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
6	1	

# **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	15.2	11.6	15
PALLET	600	48	40	45.08

