HIDFA-30S-H-E26-8CCT-BYP

Project:	Туре:	Prepared By:	Date:
	UPC: 192552005128	Adjustable wattage Integral driver enal need for an externa Rated for use in en 4kV surge protectio 50,000-Hour lifespa	closed fixtures in dry or damp locations on built in an iendly, no mercury used ed (select models)

Technical Specifications

Performance Product Type:

HID Replacement

Input Wattage: 10W/20W/30W

Lumens (Nominal): 1,600/3,200/4,800lm

Efficacy: 160lm/W

L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency: 150W Metal Halide or High Pressure Sodium

Compliance UL Listed: Suitable for damp locations

Enclosed Fixtures: Suitable for use in enclosed fixtures LED Characteristics

Color Temperature: 3000K/4000K/5000K

Color Accuracy (CRI): >80 CRI

Electrical THD: <20%

Power Factor: >0.9

Dimmable: Yes

Flicker: <30%

Operating Temperature: -30°C to 60°C

Input Voltage: 100-277V **Operating Frequency:** 50/60Hz

Construction Bulb Shape: Wall Pack

Base Type: E26 Edison

Endcap Material: Metal

Enclosure Material: Polycarbonate

Optical Beam Angle: 180°

Installation

Installation Orientation: Horizontal RAR

HIDFA-30S-H-E26-8CCT-BYP

Technical Specifications (continued)

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
8	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	16.7	12.7	17
PALLET	384	48	40	39.94

