

**Project:**

**Type:**

**Prepared By:**

**Date:**



UPC: 192552028691

### Features and Benefits

- Replaces traditional metal halide or high pressure sodium HID lamp
- Adjustable CCT allows for in-field customization
- Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed fixtures in dry or damp locations
- AUX port for integrating individual, lamp-level controls

## Technical Specifications

### Performance

**Product Type:**

HID Replacement

**Description:**

CCT field adjustable horizontal and expandable LED lamps that make great replacements for high output area lights

**Wattage Equivalency:**

250W Metal Halide

**Input Wattage:**

80W

**Lumens (Nominal):**

11,200/12,000/11,600lm

**Efficacy:**

140/150/145lm/W

**L70 Lifespan:**

50,000-Hour LED lifespan based on IES LM-70 results

### Electrical

**THD:**

≤20%

**Power Factor:**

≥0.9

**Dimmable:**

Yes

**Input Voltage:**

100-277V

**Operating Frequency:**

50/60Hz

**Input Current @ 120V (mA):**

687mA

**Input Current @ 208V (mA):**

409mA

**Input Current @ 277V (mA):**

321mA

**Operating Temperature:**

-22°F to 140°F (-30°C to 60°C)

### Flicker:

<30%

### Surge Protection:

4kV

### LED Characteristics

**Color Temperature:**

Field adjustable via dip switch 3000K/4000K/5000K

**Color Accuracy (CRI):**

≥80 CRI

**R9 Value:**

High color performance with R9 no greater than 0

**Color Consistency:**

<6-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**

LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period



## Technical Specifications (continued)

### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

### Installation

#### Installation Method:

UL Type B, Ballast Bypass

#### Installation Orientation:

Horizontal

### Construction

#### Base Type:

EX39 Exclusionary Mogul

#### Finish:

Clear

#### Bulb Shape:

Post Top

#### Endcap Material:

Metal

#### Enclosure Material:

Polycarbonate

### Compliance

#### Listings:

UL Listed, UL Classified

#### Environment:

Suitable for use in dry and damp environments

#### Fixture Rating:

Suitable for use in enclosed fixtures

#### IP Rating:

IP64

#### Energy Star Approved:

No.

There is no product category on Energy Star for this lamp to qualify under.

#### Model Number for Certification:

H20044(HIDFA-80-H-EX39-8CCT-BYP/5SP)

#### T20 Compliant:

Not Compliant

#### California Title 24 JA8 Compliant:

Not Compliant

### California Energy Commission (CEC) Status:

Lawful for Sales in California

### RoHS:

Mercury and UV free. RoHS-compliant components.

### FCC:

Complies with Part 15B of the FCC Rules

### Other

#### Accessories:

[XFMR200-480-277](#)

Transformer 200W 480V

[SP10KV](#)

10 kV Surge protector

### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Note:

All values are typical (tolerance +/- 10%)

## Case and Pallet Dimensions

|        | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE   | 6   | 17.52       | 10.91      | 14          |
| PALLET | 144 | 48.43       | 41.34      | 41.34       |

## Dimension

