



Project:	Туре:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	117W
120V	N/A	Color Temp	5000K (Cool)
208V	N/A	Color Accuracy	74 CRI
240V	N/A	L70 Lifespan	100,000 Hours
277V	N/A	Lumens	15,212 lm
Input Watts	116.9W	Efficacy	130.1 lm/W

# **Technical Specifications**

# Compliance

# UL Listed:

Suitable for wet locations

### IESNA LM-79 &lm-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNAIm-79 and Im-80

### IP Rating:

Ingress protection rating of IP66 for dust and water

### California Title 24:

Can be used to conform with the requirements of California Title 24 Part 6.

### **DLC Listed:**

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: S-1IR0QZ

### **Electrical**

### Driver:

Class 2, 50/60Hz, 480V 4kV standard, 10kV optional

# **Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

# THD:

6.3% at 480V

### **Power Factor:**

93.5% at 480V

# Performance

# Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations at  $25^{\circ}$ C

### Wattage Equivalency:

Equivalent to 450W Pulse Start Metal Halide

# **LED Characteristics**

### LEDs:

Long-life, high-efficacy, surface-mount LEDs

# Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

# **Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

# Construction

# **Cold Weather Starting:**

The minimum starting temperature is -40°C (-40°F)

# **Maximum Ambient Temperature:**

Suitable for use in up to 40°C (104°F)

### Housing:

Precision die-cast aluminum

### **IES Classification:**

The Type IV distribution is especially suited for mounting on the sides of buildings and walls, and for illuminating the perimeter of parking areas. It produces a semicircular distribution with essentially the same candlepower at lateral angles from 90° to 270°.

### Mounting:

2 3/8" slipfitter mount with stainless steel hardware

### Lens

Diffused Polymethyl Methacrylate (PMMA)

# IVAT4-130LSF750WH/WS2



# **Technical Specifications (continued)**

# **Effective Projected Area:**

EPA = 2.1

### Finish:

Formulated for high durability and long-lasting color

# **Green Technology:**

Mercury and UV free. RoHS-compliant components.

# **Sensor Specifications**

# **Multi Level Motion Sensor:**

\*40 ft diameter coverage from 20 ft height.

# **Handheld Wireless Configuration Tool:**

Adjust settings using handheld wireless configuration tool (catalog# WSREM). Only available with 0-10V dimming driver options. <u>Handheld wireless configuration tool available here.</u>

# Optical

# **BUG Rating:**

B3 U0 G3

# Other


# Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="mailto:rable-r

# **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.





# Features 0-10V Dimming, standard 100,000-Hour LED lifespan

Ordering	g Matrix							
Family	Distribution	Lumen Output	Mounting	CRI/Color Temp	Finish	Voltage/Driver	Sensor Options	Lightcloud Option
IVA	T4	– 130L	SF	750	W	Н	/WS2	
	T2 = Type II  T3 = Type III  T4 = Type IV  T5S = Type V  Square  FT = Forward  Throw	45L = 4,500lm (38W) 75L = 7,500lm (67W) 100L = 10,000lm (94W) 130L = 13,000lm (117W) 1	PA = Universal Pole Mount WM = Wall mount SF = Slipfitter	<b>750</b> = 70CRI 5000K <b>740</b> = 70CRI 4000K <b>730</b> = 70CRI 3000K	Z = Bronze W = White G = Roadway Gray K = Black	U = 120-277V 0-10V Dimming H = 347-480V, 0-10V Dimming	Blank = No Options /WS = 8ft lens Wattstopper /WS2 = 20ft lens Wattstopper /WS4 = 40ft lens Wattstopper //PR = 7-Pin receptacle	Blank = No Lightcloud® /LC = Lightcloud® Controller <sup>2</sup>
				<sup>1</sup> Applies to Type <sup>2</sup> Applies 12				
		* All va	lues are nominal v			heet for more details.		