

Date:

## Technical Specifications (continued)

**Lens:**

Diffused Polymethyl Methacrylate (PMMA)

**Effective Projected Area:**

EPA = 0.61

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

**Installation****Mounting:**

Universal pole adapter


**Other****Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

0-10V Dimming, standard

100,000-Hour LED lifespan

| Ordering Matrix |                                                                                            |   |                                                                                               |                                                                 |                                                             |                                                          |                                                           |                                                                                                                                             |                                            |
|-----------------|--------------------------------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| Family          | Distribution                                                                               |   | Lumen Output                                                                                  | Mounting                                                        | CRI/Color Temp                                              | Finish                                                   | Driver                                                    | Sensor Options                                                                                                                              | Lightcloud Option                          |
| IVA             | T5S                                                                                        | – | 100L                                                                                          | PA                                                              | 740                                                         | G                                                        | U                                                         | /7PR                                                                                                                                        | /LC                                        |
|                 | T3 = Type III<br>T4 = Type IV<br>T5S = Type V Square<br>FT = Forward Throw<br>T2 = Type II |   | 45L = 4,500lm (38W)<br>75L = 7,500lm (67W)<br>100L = 10,000lm (94W)<br>130L = 13,000lm (117W) | PA = Universal Pole Mount<br>WM = Wall mount<br>SF = Slipfitter | 730 = 70CRI 3000K<br>740 = 70CRI 4000K<br>750 = 70CRI 5000K | Z = Bronze<br>W = White<br>G = Roadway Gray<br>K = Black | U = 120-277V 0-10V Dimming<br>H = 347-480V, 0-10V Dimming | Blank = No Options<br>/WS = 8ft lens Wattstopper<br>/WS2 = 20ft lens Wattstopper<br>/WS4 = 40ft lens Wattstopper<br>/7PR = 7-Pin receptacle | Blank = No Lightcloud®<br>/LC = Lightcloud |