



## Technical Specifications (continued)

### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Sensor Specifications

#### Multi Level Motion Sensor:

\*100 ft diameter maximum coverage from 40 ft height.

### Optical

#### BUG Rating:

B3 U0 G2

### Other



#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

0-10V Dimming, standard

100,000-Hour LED lifespan

## Ordering Matrix

| Family | Distribution   |   | Lumen Output   | Mounting  | CRI/Color Temp   | Finish  | Voltage/Driver  | Sensor Options  | Lightcloud Option  |
|--------|--|---|--|---|--|---|---|---|--|
| IVA    | T5S  | - | 100L   | SF  | 740  | W   | H   | /WS4  |  |
|        | T2 = Type II<br>T3 = Type III<br>T4 = Type IV<br>T5S = Type V<br>Square<br>FT = Forward<br>Throw |   | 45L = 4,500lm<br>(38W)<br>75L = 7,500lm<br>(67W)<br>100L =<br>10,000lm (94W)<br>130L =<br>13,000lm<br>(117W) | PA = Universal<br>Pole Mount<br>WM = Wall<br>mount<br>SF = Slipfitter | 750 = 70CRI<br>5000K<br>740 = 70CRI<br>4000K<br>730 = 70CRI<br>3000K | Z = Bronze<br>W = White<br>G = Roadway<br>Gray<br>K = Black | U = 120-277V 0-10V<br>Dimming<br>H = 347-480V, 0-10V<br>Dimming | Blank = No Options<br>/WS = 8ft lens<br>Wattstopper<br>/WS2 = 20ft lens<br>Wattstopper<br>/WS4 = 40ft lens<br>Wattstopper<br>/7PR = 7-Pin<br>receptacle | Blank = No<br>Lightcloud®<br>/LC = Lightcloud®<br>Controller |