



<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	14W
120V	N/A	Color Temp	2700K-6500K
208V	N/A	Color Accuracy	82 CRI
240V	N/A	L70 Lifespan	50,000 Hours
277V	N/A	Lumens	2,200 lm
Input Watts	14W	Efficacy	155

### Technical Specifications

<p><b>Performance</b></p> <p><b>Product Type:</b> Bluetooth-Enabled T8 Type A</p> <p><b>Input Wattage:</b> 14W</p> <p><b>Lumens (Nominal):</b> 2,200lm</p> <p><b>Efficacy:</b> 155lm/W</p> <p><b>L70 Lifespan:</b> 50,000-Hour LED lifespan based on IES LM-70 results</p> <p><b>Electrical</b></p> <p><b>THD:</b> &lt;20%</p> <p><b>Power Factor:</b> &gt;0.9</p> <p><b>Dimming:</b> Dimmable via Lightcloud Blue mobile app</p> <p><b>Operating Temperature:</b> -20 to 45°C (-4°F to 113°F)</p>	<p><b>Input Voltage:</b> 120-277V</p> <p><b>Operating Frequency:</b> 50/60Hz</p> <p><b>Construction</b></p> <p><b>Material:</b> Plastic</p> <p><b>Bulb Shape:</b> T8</p> <p><b>Nominal Length:</b> 4 ft</p> <p><b>Base Type:</b> G13, Medium Bipin</p> <p><b>Optical</b></p> <p><b>Beam Angle:</b> 150°</p> <p><b>LED Characteristics</b></p> <p><b>Color Temperature:</b> 2700K-6500K</p> <p><b>Color Accuracy (CRI):</b> 82 CRI</p>	<p><b>Compliance</b></p> <p><b>NSF Listed:</b> Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.</p> <p><b>Model Number for Certification:</b> LCBT8-14-48P-8TW-DIR-SS</p> <p><b>UL Listed:</b> Suitable for damp locations</p> <p><b>Fixture Rating:</b> Enclosed</p> <p><b>Other</b></p> <p><b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a>.</p> <p><b>Buy American Act Compliance:</b> RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.</p>
--	---	---

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	50.43	5.98	7
PALLET	1	51.42	37.87	84.84

## Dimension



## Features

Direct Connect to the Lightcloud Blue mobile app via Bluetooth, no Gateway or Hub required

Use mobile device to configure features for On/Off Control, Dim Level, Color Temperature, Schedules, Scenes, SmartShift and more.

Easy to install plug and play linear lamp that requires no rewiring, no tools, no instructions

Tunable White 2700-6500K with smooth transition between color temperatures

Circadian SmartShift Capable to sync with local sunrise/sunset

## Ordering Matrix

Family	Wattage	Length	Material	CRI/Color Temp	Wiring Method	Installation Type	SmartShift
LCBT8	14	48	P	8TW		DIR	SS

14 = 14W    48 = 4 ft    P = Plastic    8TW = 80 CRI, Tunable White    Blank = Single Ended    DIR = Ballast Compatible    SS = SmartShift