

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for High output incandescent/halogen or ceramic metal halide HID Lamps
- Commercial Grade
- Large metal heatsink for optimal heat dissipation
- In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast.
- Produces rich and vibrant colors >90CRI
- Energy efficient replacement for incandescent and halogen PAR lamps
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry and damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- Title 20 Compliant, Energy Star Compliant, UL Listed
- Non-dimmable

Technical Specifications		
<p>Performance</p> <p>Product Type: Commercial PAR</p> <p>Input Wattage: 19W</p> <p>Lumens (Nominal): 1,800lm</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p> <p>Wattage Equivalency: 75W Halogen / 39W CMH</p> <p>LED Characteristics</p> <p>Color Accuracy (CRI): 90 CRI</p> <p>Color Temperature: 4000K</p> <p>Electrical</p> <p>Power Factor: >0.9</p>	<p>Dimmable: Non-Dim</p> <p>Input Voltage: 120-277V AC</p> <p>Operating Frequency: 60 Hz</p> <p>Operating Temperature: -20°C to 45°C (-4°F to 113°F)</p> <p>Construction</p> <p>Bulb Shape: PAR30L</p> <p>Enclosure Material: Die Cast Aluminum</p> <p>Housing Finish: White</p> <p>Base Type: E26 Edison</p>	<p>Optical</p> <p>Beam Angle: 40°</p> <p>MBCP: 3400</p> <p>Other</p> <p>Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.</p> <p>Compliance</p> <p>Listings: UL Listed</p> <p>Environment/Fixture Rating: Damp / Open</p>

Technical Specifications (continued)

Energy Star Approved:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2366168

T20 Compliant:

Yes, Title 20 Tier 2

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Model Number for Certification:

P10029(PAR30L-19-E26-940-40D-ND)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
8	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	1	0	0	0
PALLET	720	0	0	0

Dimension

