

Project: Type: Prepared By: Date:



Features and Benefits

Replacement for high-output incandescent/halogen or ceramic metal

Adjustable CCT to choose from 3000/4000/5000K

Rated for use in enclosed fixtures in dry, damp, or wet locations

90+CRI provides high quality color rendering

Shatterproof enclosure for rugged applications

Technical Specifications

Performance

Product Type:

PAR

Input Wattage:

19W

Lumens (Nominal):

1,800lm

Efficacy:

163.6lm/W

L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:

150W Halogen

Compliance

Enclosed Fixtures:

Suitable for use in enclosed fixtures

LED Characteristics

Color Temperature: 3000K/4000K/5000K

Color Accuracy (CRI):

90 CRI

Electrical

THD:

<20%

Power Factor:

0.9

Dimmable:

Yes

Operating Temperature:

-20°C to 45°C (-4°F to 113°F)

Input Voltage:

120V

Operating Frequency:

60 Hz

Construction

Bulb Shape:

PAR38

Base Type:

E26 Edison

Endcap Material:

Aluminum

Enclosure Material:

Plastic

Optical

Beam Angle:

40°

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.



Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	20.3	15.4	20
PALLET	432	47.24	41.34	37.01

