

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



**Features and Benefits**

- Replaces 13W CFL Lamps
- Plug and Play on existing magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with Gx23 base installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- 5 Year No Compromise Warranty

Technical Specifications		
<p><b>Performance</b></p> <p><b>Product Type:</b> Compacts</p> <p><b>Input Wattage:</b> 5.5W</p> <p><b>Lumens (Nominal):</b> 600lm</p> <p><b>Efficacy:</b> 109.1lm/W</p> <p><b>L70 Lifespan:</b> 50,000-Hour LED lifespan based on IES LM-70 results</p> <p><b>Wattage Equivalency:</b> 11W CFL</p> <p><b>LED Characteristics</b></p> <p><b>Color Accuracy (CRI):</b> 80 CRI</p> <p><b>Color Temperature:</b> 5000K</p>	<p><b>Construction</b></p> <p><b>Material:</b> Polycarbonate</p> <p><b>Bulb Shape:</b> PLS-Horizontal</p> <p><b>Base Type:</b> Gx23</p> <p><b>Optical</b></p> <p><b>Beam Angle:</b> 120°</p> <p><b>Electrical</b></p> <p><b>Power Factor:</b> &gt;0.9</p> <p><b>Input Voltage:</b> 120-277V</p> <p><b>Operating Temperature:</b> -20°C to 45°C (-4°F to 113°F)</p> <p><b>Compliance</b></p> <p><b>Enclosed Fixtures:</b> Suitable for use in enclosed fixtures</p>	<p><b>UL Listed:</b> Suitable for damp locations</p> <p><b>UL Classified:</b> Yes</p> <p><b>Model Number for Certification:</b> T10369(PLS-5.2-H-850-HYB)</p>



**Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	7.2	5.4	3
PALLET	0	0	0	0

**Dimension**

