PR4-11-20WT





Project:	Туре:
Prepared By:	Date:

# **Technical Specifications**

#### Compliance

#### **CSA Listed:**

Suitable for wet locations

# Performance

#### Description:

Steel pole 4" round 11 gauge 20 foot welded tenon square base

# Construction

# Shaft:

46,000 p.s.i. minimum yield.

#### **Hand Holes:**

Reinforced with grounding lug and removable cover

# **Base Plates:**

Slotted base plates 36,000 p.s.i.

#### Color:

Bronze powder coating

#### Tenor

Welded 2 3/8" tenon included

#### Height:

20 ft

# Gauge:

11

#### Wall Thickness:

1/8"

### Shaft Size:

4"

#### **Anchor Bolt Templates:**

WARNING Template must be printed on 11"  $\times$  17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available online.

# Max EPA's/Max Weights:

70MPH 7.4 ft/500 lb. 80MPH 5.5 ft/460 lb. 90MPH 3.3 ft/430 lb. 100MPH 2.1 ft/320 lb.

110MPH 1.1 ft/200 lb. 120MPH 0.5 ft/110lb

# Accessories:

Base/Cap: <u>BASE-R4</u> Anchor Bolts: <u>BOLT4/11</u>

# Other

#### Terms of Sale:

Pole Terms of Sale is available online.

#### **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



# Dimensions 20' 6,096 mm

#### Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application

# Ordering Matrix

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
Р	R	4	11	20	WT
	R = Round TR = Tapered Round	<b>4</b> = 4" <b>5</b> = 5" <b>6</b> = 6" <b>7</b> = 7" <b>8</b> = 8"	<b>7</b> = 7 <b>11</b> = 11	10 = 10' 15 = 15' 20 = 20' 25 = 25' 30 = 30'	D2 = Drilled WT = Welded Tenon