



Project:	Туре:
Prepared By:	Date:

Technical Specifications

Compliance

CSA Listed:

Suitable for wet locations

Performance

Description:

Steel pole 4" round 11 gauge 25 foot welded tenon square base

Construction

Shaft:

46,000 p.s.i. minimum yield.

Hand Holes:

Reinforced with grounding lug and removable cover

Base Plates:

36,000 p.s.i. minimum yield.

Color:

Bronze powder coating

Height:

25 ft

Gauge:

11

Wall Thickness:

1/8"

Shaft Size:

4"

Anchor Bolt Templates:

WARNING Template must be printed on 11" \times 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available online.

Max EPA's/Max Weights:

70MPH 4.5 ft/400 lb. 80MPH 2.4 ft/310 lb. 90MPH 1.1 ft/200 lb. 100MPH 0.1 ft/120 lb

Accessories:

Base/Cap: <u>BASE-R4</u> Anchor Bolts: <u>BOLT4/11</u>

Other

Terms of Sale:

Pole Terms of Sale is available online.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



Dimensions 25' 7,620 mm

Features

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application

Ordering Matrix

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
Р	R	4	11	25	WT
	R = Round TR = Tapered Round	4 = 4" 5 = 5" 6 = 6" 7 = 7" 8 = 8"	7 = 7 11 = 11	10 = 10' 15 = 15' 20 = 20' 25 = 25' 30 = 30'	D2 = Drilled WT = Welded Tenon