



Project: Type:

Prepared By: Date:

Square steel poles with welded tenon included for use with floodlights. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 198.0 lbs

# **Technical Specifications**

#### Compliance

#### CSA Listed:

Suitable for wet locations

#### Construction

# Shaft:

46,000 p.s.i. minimum yield.

### **Hand Holes:**

Reinforced with grounding lug and removable cover

### **Base Plates:**

36,000 p.s.i. minimum yield.

#### **Shipping Protection:**

All poles are shipped in individual corrugated cartons to prevent finish damage

# Color:

Bronze powder coating

#### Height:

25 ft

### Gauge:

11

### Wall Thickness:

1/8"

### Shaft Size:

4"

## **Hand Hole Dimensions:**

3" x 5"

# Bolt Circle:

8 1/2"

#### **Base Dimension:**

8"

# Weight:

198 lbs

### **Anchor Bolt:**

Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.

## **Anchor Bolt Templates:**

WARNING Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available online.

### **Pre-Shipped Anchor Bolts:**

Bolts can be pre-shipped upon request for additional freight charge

# Max EPA's/Max Weights:

70MPH 4.3 ft/275 lb. 80MPH 1.7 ft/270 lb

### Other


# Terms of Sale:

Pole Terms of Sale is available online.

# **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.





#### **Features**

Designed for ground mounting

Heavy duty TGIC polyester coating

Reinforced hand holes with grounding lug and removable cover for easy wiring access

Pole caps, base covers & bolts are sold separately

Custom manufactured for each application