



Color: Bronze

Weight: 216.9 lbs

Project:

Type:

Prepared By:

Date:

Technical Specifications

Compliance

CSA Listed:

Suitable for wet locations

Performance

Description:

Steel pole 6" taper 7 gauge 20 foot drilled two sides square base

Construction

Base Shaft Diameter:

6"

Top Diameter:

3.20"

Hand Holes:

Reinforced with grounding lug and removable cover

Base Plates:

36,000 p.s.i. minimum yield.

Color:

Bronze powder coating

Height:

20 ft

Gauge:

7

Wall Thickness:

3/16"

Anchor Bolt Templates:

WARNING Template must be printed on 12" x 18" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available [online](#).

Max EPA's/Max Weights:

70MPH 28.1 ft/700 lb.
80MPH 20.3 ft/700lb.
90MPH 15.1 ft/690 lb.
100MPH 11.4 ft/670 lb.
110MPH 8.6 ft/680 lb.
120MPH 6.3 ft/670lb.
130MPH 4.8 ft/670 lb.
140MPH 3.3 ft/650 lb.
150MPH 2.5 ft/640 lb

Accessories:


Base/Cap: [BCK-RT6/20](#)
Anchor Bolts: [BOLT5-8](#)

Other

Terms of Sale:

Pole Terms of Sale is available [online](#).

Dimensions



Features

- Designed for ground mounting
- Heavy duty TGIC polyester coating
- Reinforced hand holes with grounding lug and removable cover for easy wiring access
- Pole caps, base covers & bolts are sold separately
- Custom manufactured for each application

Ordering Matrix

Family	Shape	Size	Gauge	Height	Drilled/Welded Tenon
P	TR	6	7	20	D2
R = Round		4 = 4"	7 = 7	10 = 10'	D2 = Drilled
TR = Tapered Round		5 = 5"	11 = 11	15 = 15'	WT = Welded Tenon
		6 = 6"		20 = 20'	
		7 = 7"		25 = 25'	
		8 = 8"		30 = 30'	