

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	29W
120V	0.24A	Color Temp	4000K (Neutral)
208V	0.15A	Color Accuracy	84 CRI
240V	0.13A	L70 Lifespan	100,000 Hours
277V	0.11A	Lumens	3,991 lm
Input Watts	29W	Efficacy	137.6 lm/W

Technical Specifications

Lightcloud

Lightcloud Controller Installed:
 Fixture, Zone, and plug-load control from one powerful device. Capable of switching, 0-10V dimming, power monitoring. Can also be used to extend the range of the Lightcloud mesh network. Attach to fixture, junction box, or electrical panel. [Learn more about Lightcloud.](#)

Compliance

UL Listed:
 Suitable for damp locations

Electrical

Driver:
 Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.24A, 0.15A, 0.13A, 0.11A

THD:
 8.5% at 120V, 11.8% at 277V

Power Factor:
 99.6% at 120V, 92.9% at 277V

Surge Protection:
 4kV

Construction

Housing:
 Steel sheet metal

Ambient Temperature:
 Suitable for use in up to 40°C (104°F)

Reflector:
 High-reflectance, powder-coated finish, optimized for uniform light distribution

Mounting:
 Recessed ceiling

Lens:
 Polycarbonate lens

Finish:
 Formulated for high durability and long-lasting color

Green Technology:
 Mercury and UV free. RoHS-compliant components.

Other

Note:
 All values are typical (tolerance +/- 10%)

Buy American Act Compliance:
 RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

LED Characteristics

LEDs:
 Long-life, high-efficacy, surface-mount LEDs

Color Stability:
 LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period


Color Uniformity:
 RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance

Lifespan:
 100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:
 Equivalent to (1) F17T8 or (1) F14T5

Dimensions



Features

- Troffer Retrofit can be installed in under 3 minutes by 1 person
- Frosted polycarbonate lens provides a uniform distribution and reduces glare
- 0-10V dimming, standard
- 5-Year, No-Compromise Fixture Warranty and 10-Year, No-Compromise Lightcloud Warranty

Ordering Matrix

Family	Size		Wattage	Color Temp	Finish	CRI	Dimming Driver	Options
RTLED	1X4	-	29	N	W		/D10	/LC
	1X4 = 1'x4'		19 = 19W (2x2, 1x4)	Blank = 5000K Cool	W = White	Blank = 80 CRI	/D10 = 0-10V Dimming	Blank = No Options
	2X2 = 2'x2'		29 = 29W (2x2, 1x4)	N = 4000K Neutral		/HC = 90 CRI		/LC = Lightcloud® Controller
	2X4 = 2'x4'		39 = 39W (2x4)	YN = 3500K Warm		(4000K only) ¹		/E2 = Battery Backup
			49 = 49W (2x4)	Neutral				/MVS = Microwave Occupancy Sensor
				Y = 3000K Warm				/MVS/E2 = Microwave Occupancy Sensor w/ Battery Backup

¹ 4000K only