



## Technical Specifications (continued)

### Performance


#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Wattage Equivalency:

Equivalent to (2) F17T8 or (2) F24T5

### Dimensions



### Features

- Troffer Retrofit can be installed in under 3 minutes by 1 person
- Frosted polycarbonate lens provides a uniform distribution and reduces glare
- 0-10V dimming, standard
- 5-Year, No-Compromise Fixture Warranty and 10-Year, No-Compromise Lightcloud Warranty

### Ordering Matrix

Family	Size	Wattage	Color Temp	Finish	CRI	Dimming Driver	Options
RTLED	2X2	19	N	W	/HC	/D10	/LC
	1X4 = 1'x4' 2X2 = 2'x2' 2X4 = 2'x4'	19 = 19W (2x2, 1x4) 29 = 29W (2x2, 1x4) 39 = 39W (2x4) 49 = 49W (2x4)	Blank = 5000K Cool N = 4000K Neutral YN = 3500K Warm Neutral Y = 3000K Warm	W = White	Blank = 80 CRI /HC = 90 CRI (4000K only) <sup>1</sup>	/D10 = 0-10V Dimming	Blank = No Options /LC = Lightcloud® Controller /E2 = Battery Backup /MVS = Microwave Occupancy Sensor /MVS/E2 = Microwave Occupancy Sensor w/ Battery Backup

<sup>1</sup> 4000K only