

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	29W
120V	0.24A	Color Temp	3500K (Warm Neutral)
208V	0.15A	Color Accuracy	84 CRI
240V	0.13A	L70 Lifespan	100,000 Hours
277V	0.11A	Lumens	3,653 lm
Input Watts	29.4W	Efficacy	124.3 lm/W

Technical Specifications

Compliance

UL Listed:
Suitable for damp locations

Electrical

Driver:
Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.24A, 0.15A, 0.13A, 0.11A

THD:
17.8% at 120V, 12.3% at 277V

Power Factor:
98.3% at 120V, 93% at 277V

Battery Backup:
Battery backup will operate the fixture for 90 minutes if power fails. Wired for 120.

Surge Protection:
4kV

Construction

Housing:
Steel sheet metal

Ambient Temperature:
Suitable for use in up to 40°C (104°F)

Reflector:
High-reflectance, powder-coated finish, optimized for uniform light distribution

Mounting:
Recessed ceiling

Lens:
Polycarbonate lens

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Other Note:
All values are typical (tolerance +/- 10%)

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:
RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

LED Characteristics:
LEDs:
Long-life, high-efficacy, surface-mount LEDs


Color Stability:
LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance:
Lifespan:
100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:
Equivalent to (3) F17T8 or (3) F14T5

Dimensions



Features

- Troffer Retrofit can be installed in under 3 minutes by 1 person
- Frosted polycarbonate lens provides a uniform distribution and reduces glare
- 0-10V dimming, standard
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size		Wattage	Color Temp	Finish	CRI	Dimming Driver	Options
RTLED	2X2	-	29	YN	W		/D10	/E2
	1X4 = 1'x4'		19 = 19W (2x2, 1x4)	Blank = 5000K Cool	W = White	Blank = 80 CRI	/D10 = 0-10V Dimming	Blank = No Options
	2X2 = 2'x2'		29 = 29W (2x2, 1x4)	N = 4000K Neutral		/HC = 90 CRI		/LC = Lightcloud® Controller
	2X4 = 2'x4'		39 = 39W (2x4)	YN = 3500K Warm		(4000K only) ¹		/E2 = Battery Backup
			49 = 49W (2x4)	Neutral				/MVS = Microwave Occupancy Sensor
				Y = 3000K Warm				/MVS/E2 = Microwave Occupancy Sensor w/ Battery Backup

¹ 4000K only