

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	70W
120V	0.62A	Color Temp	4000K (Neutral)
208V	0.34A	Color Accuracy	85 CRI
240V	0.30A	L70 Lifespan	100,000 Hours
277V	0.29A	Lumens	10,134 lm
Input Watts	69.4W	Efficacy	146 lm/W

Technical Specifications

Compliance

UL Listed:
Marine Listed Outside Type (Saltwater)

UL 94:
5VA flame classification

IP Rating:
Ingress protection rating of IP66 for dust and water

NEMA Rating:
4X, protected against corrosion

DLC Listed:
This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: PNNZDUCJ (Stairwell and Passageway Luminaires)
DLC Product Code: PA9HX5UJ (High-Bay Luminaires for Commercial and Industrial Buildings)
DLC Product Code: P8I3Z7RC (Direct Linear Ambient Luminaires)

Construction

Length:
8 ft

Reflector:
Specular polycarbonate

Housing:
IK09 impact-resistant polycarbonate with 5VA flame rating*
1/2" openings for conduit and bushing/cord entry
*Polycarbonate is affected by cleaning agents or other liquids containing partial solvents such as low molecular weight aldehydes and ethers, ketones, esters, aromatic hydrocarbons and perchlorinated hydrocarbons. [Click here for a detailed list of damaging chemicals.](#)

Mounting:
Quick-mount, surface, stainless steel spring clips and V-Hook with bracket screws are supplied. 3 additional mounting accessory kits available.

Lens:
Textured, diffuse polycarbonate lens for low glare and maximum protection

Gaskets:
EVA

Cold Weather Starting:
The minimum starting temperature is -30°C (-22°F)

Maximum Ambient Temperature:
Suitable for use in up to 40°C (104°F)

Finish:
Formulated for high durability and long-lasting color

Cord:
Comes standard with 6 ft cord

LED Characteristics

LEDs:
Long-life, high-efficacy, surface-mount LEDs

Color Uniformity:
RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Electrical

Driver:
Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.62A, 208V: 0.34A, 240V: 0.30A, 277V: 0.29A

THD:
1.19% at 120V, 3.38% at 277V

Power Factor:
99.8% at 120V, 94.4% at 277V

Surge Protection:
4kV

Technical Specifications (continued)

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Other


Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- UL Marine Listed
- NSF certified for use in food-preparation facilities
- American Bureau of Shipping (ABS) approved
- Impact-resistant linear washdown
- Ideal for tunnels and stairwells
- Mounting options:
 - Chain, junction box, angled surface mount, ceiling mount or vandal-resistant surface mount
- IP66 AND NEMA 4X ratings protect against dust, water ingress & corrosion
- 5-Year, No-Compromise Warranty
- 100,000-Hour LED lifespan