SLEDR5DCW

RAB



Round LED Step Lights for solar applications or other 10-30VDC systems. Up to 85% more efficient than line voltage AC solutions. Available in 5W round shaped step lights. Solar panel, battery and controls by others.

Color: White

Weight: 1.2 lbs

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations. Suitable for mounting within 4ft. of the ground.

IESNA LM-79 &lm-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNAIm-79 andIm-80

Electrical

THD: 11.6% at 120V, 21% at 277V

Electrical Input Specifications: MaxW = 5.1W, Input Volts = 10-30V DC, Input Amps = 0.51 - 0.17A.

Surge Protection:

1000 Volts

Performance

Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Wattage Equivalency:

Equivalent to 13W CFL or 60W Incandescent

Construction

Finish: Formulated for high durability and long-lasting color

Cold Weather Starting: The minimum starting temperature is -40°C (-40°F)

Maximum Ambient Temperature: Suitable for use in up to 40°C (104°F)

Green Technology:

Mercury and UV free. RoHS-compliant components.

Housing:

Precision die-cast aluminum housing and mounting plate (junction box not included)

Gaskets: High-temperature silicone

LED Characteristics

Color Consistency: 7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 100,000 hours of operation

Proje	ared By:	Туре:	
Prep	ared By:	Date:	
Driver Ir	nfo	LED Info	
Туре	DC to DC	Watts 5W	
120V	N/A	Color Temp 5000K (Cool)	
208V	N/A	Color Accuracy 68 CRI	
240V	N/A	L70 Lifespan 100,000 Hours	
277V	N/A	Lumens 213 lm	

Color Temperature:

5000K

Input Watts 5.2W

Other

Patents: The design of the SLED Lights are protected by U.S. Pat. D612,974, CA Pat. 133100, and China Pat. ZL201030129138.4.

Efficacy

41 lm/W

Equipment:

Solar panel, battery and controls by others

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

SLEDR5DCW



