

Contemporary surface-mount fixtures with a slim design. Multiple sizes and form factors available, in both 80 and 90 CRI models. 120V and 120-277V offered.

Color: White

Weight: 2.4 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	25W
120V	0.23A	Color Temp	Field Adjustable
208V	0.15A		2700K/3000K/3500K/4000K/5000K
240V	0.13A	Color Accuracy	90 CRI
277V	0.12A	L70 Lifespan	50,000 Hours
Input Watts	25W	Lumens	1,800-1,960 lm
		Efficacy	72-78 lm/W

## Technical Specifications

### Performance

#### Description:

This surface linear downlight offers a sleek, modern look for any application. Offered in various unique form factors, 5 color temperatures to choose from, universal voltage (120-277V) and dimming options available.

#### Product Type:

Surface & Flush Mounts

#### Input Wattage:

25W

#### Efficacy:

5000K: 78lm/W  
 4000K: 78lm/W  
 3500K: 76lm/W  
 3000K: 74lm/W  
 2700K: 72lm/W

#### L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

#### Dimming:

Yes, See Dimmer Compatibility List

#### Wattage Equivalency:

Equivalent to 40W CFL

### Compliance

#### UL Listed:

Suitable for damp locations

#### Energy Star Approved:

ENERGY STAR® Version 2.2 Certified

#### Energy Star ID:

2396879

#### Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

### Electrical

#### THD:

≤30%

#### Power Factor:

≥0.9

#### Operating Frequency:

50/60Hz

### Construction

#### Material:

Metal

#### Trim Style:

Smooth Trim

### Mounting:

Surface mount

### Operating Temperature Range:

-20°C - 40°C (-4°F - 104°F)

### Other


#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

**Dimensions**



**Features**

- Select from 5 field-adjustable color temperatures 2700K, 3000K, 3500K, 4000K, or 5000K
- Suitable for indoor applications in dry and damp environments
- Dimmable, see Dimmer Compatibility List
- Meets California Title 24 requirements
- 50,000 life hours
- 5-Year, no compromise warranty

**Ordering Matrix**

Family	Size	CRI/Color Temp	Finish	Voltage/Dimming
SML	2			

2 = 2 ft, 25W    Blank = 90 CRI, CCT Adjustable    Blank = White    Blank = 120-277V, TRIAC  
 3 = 3 ft, 35W  
 4 = 4 ft, 45W