


Project: Type: Prepared By: Date:



UPC: 192552043564

### **Features and Benefits**

Each LED bulb delivers 1200 lumens for a total of 12,000 lumens per fixture

Durable 100ft. SPT-2W 18/2 AWG power cord, with integrated hanging hook on each lamp

ANTI-UV protection for sun exposure and IP65 rated

Linkable strands up to 400W; a total of 4 fixtures

120V AC input voltage

# **Technical Specifications**

#### Performance

### **Product Type:**

**LED Temporary String Light** 

# Description:

Upgrade traditional work lights with efficient, portable LED string lights.

### Wattage Equivalency:

300W Incandescent

## Input Wattage:

100W

### Lumens:

12,000lm

# Efficacy:

120lm/W

### L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

### **Electrical**

# Driver:

Constant Current

### **Power Factor:**

0.5

### Dimmable:

No

# Input Voltage:

120V

# Operating Frequency:

60 Hz

## Input Current @ 120V (mA):

1,430mA

# **Operating Temperature:**

-40°F to 104°F (-40°C to -40°C)

### Flicker:

30%

# **Sensor Settings**

### **Surge Protection:**

1kV

### **LED Characteristics**

### Beam Angle:

120°

# **Color Temperature:**

5000K

## Color Accuracy (CRI):

>80 CRI

## **Color Consistency:**

<7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

### Installation

### Mounting:

Integrated hanging hook

### Base Type:

SPT-2W 18/2AWG power cord, high-impact design ANSI 2-prong plug and receptacle with weatherproof cover. No ground required; housing is made of polycarbonate material

# Linkable:

Linkable strands up to 400W

# STRING17-100



# **Technical Specifications (continued)**

### Construction

### Lamp Shape:

Oval lamp with frosted lens

#### Finish:

Orange

### **Enclosure Material:**

Polycarbonate

### Compliance

### ETL Listed:

This product has been tested by Intertek and found in compliance with accepted national standards.

### **Environment:**

Suitable for use indoors and outdoors in dry, damp, or wet environments.

## **Fixture Rating:**

Suitable for use in enclosed fixtures. Suitable for use in open fixtures.

### IP Rating:

IP65

### **Energy Star Approved:**

No

# DLC Listed:

No

# **Certification Model Number:**

STRING17-100

### California Title 20 Compliant:

No

## California Title 24 JA8 Compliant:

No

# California Energy Commission (CEC) Status:

Lawful for Sales in California

### **NSF Listed:**

No

#### RoHS:

Mercury and UV free. RoHS-compliant components.

## FCC:

Complies with Part 15 of the FCC Rules

# Other

### 3 Yr Limited Warranty:

The RAB 3-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty



# **Case and Pallet Dimensions**

|        | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE   | 2   | 17.17       | 17.17      | 6.3         |
| PALLET | 72  | 53.15       | 35.43      | 47.24       |

