




Project:	Type:
Prepared By:	Date:

Driver Info	LED Info
Type Constant Current	Watts 40/30/20W
120V 0.15A/0.16A/0.23A/0.24A/0.31A/0.32A	Color Temp 3500K/4000K/5000K
208V 0.11A/0.14A/0.18A	Color 84-85 CRI
240V 0.09A/0.12A/0.16A	Accuracy
277V 0.08A/0.11A/0.14A	L70 Lifespan 100,000 Hours
Input 18.7-38.1W	Lumens 2924-5815 lm
Watts	Efficacy 146.8-160.8 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:

Field Adjustable Light Output:
40/30/20W (factory default 20W)
Color temperature selectable by 3500/4000/5000
(factory default 4000K)

Compliance

UL Listed:

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA lm-79 and lm-80.

CCEA Compliant:

Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: S-X0GP4X

LED Characteristics

LEDs:

Long-life, high-efficacy, discrete, surface-mount LEDs

Color Consistency:

4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance

Lifespan:

100,000-Hour LED lifespan based on IES lm-80 results and TM-21 calculations

Electrical

Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz:
40W: 120V: 0.333A, 208V: 0.192A, 240V: 0.167A, 277V: 0.144A
30W: 120V: 0.250A, 208V: 0.144A, 240V: 0.125A, 277V: 0.108A
20W: 120V: 0.167A, 208V: 0.096A, 240V: 0.083A, 277V: 0.072A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

9.82% at 120V, 6.68% at 277V

Power Factor:

99.3% at 120V, 95.3% at 277V

Aux Power Supply:

Yes

Dim to Off:

Yes

Surge Protection:

DM: 1 kV
CM: 2 kV

Battery Backup:

Battery backup will operate the fixture for 90 minutes if power fails. Wired for 120-277V.

Battery Backup Light Loss Factor:

40W: 10%
30W: 13.3%
20W: 20%

Technical Specifications (continued)

Construction

Cold Weather Starting:

The minimum starting temperature is 0°C (32°F)

Maximum Ambient Temperature w/Battery

Backup:

Suitable for use in up to 104°F (40°C)

Lens:

Polycarbonate lens

Housing:

Metal

Reflector:

Metal

Green Technology:

Mercury and UV free. RoHS-compliant components.

Installation

Mounting:

Surface mounting standard. V-Hooks and Chain mounting available (ordered separately, SR VHOOK KIT).

Lightcloud

Lightcloud Blue Sensor Installed:

Lightcloud Blue is a Bluetooth Mesh wireless lighting control system that allows you to control RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and large commercial applications using the Lightcloud Blue mobile app. Each device in a system can communicate with any other device, eliminating the need for a Gateway or Hub and maximizing the control system's reach.

DLC system - N1XMLOEATBA (Interior);
NHCZ2BIA17L (Exterior)


Learn more at
www.rablighting.com/feature/new-lightcloud-blue.

Other

5-Year Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- 100,000-Hour LED lifespan
- 120-277V standard
- 0-10V dimming, standard
- 5-Year, limited warranty

Ordering Matrix

Family	Size/Wattage	Color Temp	Finish	Driver	Controls	Battery Backup
STRP	4H				/LCBS	/E
	2 = 2 ft, 10/8/6W 2H = 2 ft, 20/15/10W 4 = 4 ft, 20/15/10W 4H = 4 ft, 40/30/20W	Blank = 3500/4000/5000K CCT Adjustable	Blank = White	Blank = 120-277V, 0-10V Dimming	Blank = None /MVS = Microwave Occupancy Sensor /PIR = Passive Infrared Occupancy Sensor /LCBS = Lightcloud Blue w/PIR Sensor /LCBS/MVS = Lightcloud Blue w/MVS Sensor	Blank = None /E = Battery Backup ¹

¹ Only available for 4 ft models