



Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	30W
120V	0.28A	Color Temp	2700K/3000K/3500K/4000K/5000K
208V	N/A	Color Accuracy	90 CRI
240V	N/A	L70 Lifespan	50,000 Hours
277V	N/A	Lumens	2,250-2,450 lm
Input Watts	30W	Efficacy	75-82 lm/W

Technical Specifications		
Performance Product Type: Edge-lit Surface Mount Input Wattage: 30W Lumens (Nominal): 5000K: 2,300lm 4000K: 2,450lm 3500K: 2,450lm 3000K: 2,350lm 2700K: 2,250lm Efficacy: 5000K: 77lm/W 4000K: 82lm/W 3500K: 82lm/W 3000K: 78lm/W 2700K: 75lm/W L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results Wattage Equivalency: Equivalent to 150W Incandescent Electrical Driver: Constant Current, 50/60 Hz 120V, 120V: 0.28A	THD: ≤20% Power Factor: ≥0.9 Dimmable: Yes, TRIAC/ELV dims down to 10%. See Dimmer Compatibility List. Input Voltage: 120V Operating Frequency: 50/60Hz Operating Temperature: -4°F to 104°F (-20°C to 40°C) Surge Protection: 2.5kV LED Characteristics Color Temperature: Field Adjustable: 2700K,3000K,3500K,4000K,5000K Color Accuracy (CRI): >90 CRI	R9 Value: High color performance with R9 greater than or equal to 50 Color Consistency: 4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period Color Uniformity: RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017. Installation Mounting: Surface Mount Construction Size: 19" Shape: Round

Technical Specifications (continued)**Finish:**

Formulated for high durability and long-lasting color

Housing Material:

Metal

Trim Style:

Smooth

Lens:

Frosted lens constructed from polycarbonate material diffuses light evenly and smoothly

Compliance**Listings:**

UL Listed

Environment:

Suitable for use in indoor and outdoor application in dry, damp, and wet environments

UV Protection:

Fade-resistant powder spray polyester

Energy Star Approved:

This product is ENERGY STAR® Version 2.2 Certified

California Energy Commission (CEC) Status:

Lawful for Sales in California

NEC Compliant:

Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C3).

IESNA LM-79 & lm-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA lm-79 and lm-80

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

Other**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Note:

All values are typical (tolerance +/- 10%)

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Select from 5 field-adjustable color temperatures 5000K, 4000K, 3500K, 3000K, or 2700K

Suitable for indoor/outdoor applications in dry, damp, or wet environments

TRIAC/ELV dims down to 10%. See Dimmer Compatibility List.

Meets California Title 24 requirements

50,000-Hour LED lifespan

5-Year, No-Compromise Warranty

120V