SWISH2X4-49YN/D10/CP



Project: Type: **Prepared By:** Date:

Driver Info		LED Info		
Туре	Constant Current	Watts	49W	
120V	0.43A	Color Temp	3500K (Warm	
208V	0.25A	color remp	Neutral)	
240V	0.21A	Color Accuracy	83 CRI	
277V	0.18A	L70 Lifespan	100,000 Hours	
Input Watts	50.6W	Lumens	7,340 lm	
		Efficacy	145.1 lm/W	

Technical Specifications

Compliance

CCEA Compliant:

Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

UL Listed:

Suitable for damp locations

IESNA LM-79 &lm-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNAlm-79 and Im-80

DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PU72DJXV

Electrical

Driver:

Class 2, Constant Current, 120-277V, 50/60Hz, 120V: 0.43A, 208V: 0.25A, 240V: 0.21A, 277V: 0.18A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD: 5.92% at 120V, 8.66% at 277V

Power Factor: 99.8% at 120V, 97.5% at 277V

Surge Protection: 2.5kV

Construction

Cold Weather Starting: The minimum starting temperature is -20°C (-4°F)

Ambient Temperature: Suitable for use in up to 40°C (104°F)

IC Rated: Suitable for direct contact with insulation

Housing: Die-formed, 20-gauge, cold-rolled steel

Mounting:

Integral T-grid clips make installation easy and secure

Reflector:

High-reflectance, powder-coated finish, optimized for uniform light distribution

Lens: Snap-in, frosted polycarbonate lens

Finish: Formulated for high durability and long-lasting color

Green Technology: Mercury and UV free. RoHS-compliant components.

LED Characteristics

I FDs: Long-life, high-efficacy, surface-mount LEDs

Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Performance

Lifespan: 100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

SWISH2X4-49YN/D10/CP

Technical Specifications (continued)

Other

Warranty:


RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

Patents:

This design is protected by patents pending in US, Canada, China, Taiwan and Mexico

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



Ordering Matrix

Family Size	Wattage	Color Temp	Driver	Options	Chicago Penum
SWISH 2X	- 49	YN	/D10		/CP
2X4 = 2 2X2 = 2		Blank = 5000K Cool N = 4000K Neutral YN = 3500K Warm Neutral Y = 3000K Warm	/D10 = 0-10V Dimming	Blank = No Option /E2 = Battery Backup /LC = Lightcloud® Controller /LC/E2 = Lightcloud® Controller w/ Battery Backup /MVS = Microwave Occupancy Sensor /MVS/E2 = Microwave Occupancy Sensor w/ Battery Backup	Blank = Standard /CP = Chicago Plenum

Need help? Tech help line: (888) 722-1000 Email: sales@rablighting.com Website: www.rablighting.com

Copyright © 2023 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

RAB

SWISH2X4-49YN/D10/CP

